

Hurricane Resistant Window Product Selection Guide

	MODEL	DESIGN PRESSURE RATING (PSF POS.+)	DESIGN PRESSURE RATING (PSF NEG.-)	WATER PRESSURE TEST (PSF)	FRAME DEPTH	CONFIGURATION	TEST STANDARD	WIND ZONE	MISSILE DESIGNATION	TRIM / CLIP
hung										
SINGLE HUNG	I9100	80	110	12	3-1/4"	O/X	TAS	4	LM	S-1648 / S-1649
SINGLE HUNG	AA®3350	50	50	15	3-1/2"	O/X	TAS	3	SM-D / LM-D	
SINGLE HUNG	8400TL	90	90	15	4"	O/X	TAS	4	SM-D / LM-D	
sliding										
HORIZONTAL SLIDING	I6800	50	50	10	3-1/4"	OXO	TAS	4	LM-D	
HORIZONTAL SLIDING	8400TL	90	90	15	4"	OX	TAS	4	SM / LM	
casement										
CASEMENT OUTSWING	AA®900	100	110	15	2-5/8"	X	TAS	4	SM-D	
CASEMENT OUTSWING	AA®900	90	90	15	2-5/8"	X	TAS	4	LM-D	
CASEMENT OUTSWING	I3100	80	80	15	3-1/4"	X	TAS	4	LM-D	S-019 / S-020
CASEMENT OUTSWING	NX-3100I	100	100	15	3-1/4"	X	TAS	4	LM-D	S-1542 / S-1543
projected										
PROJECTED IN	7225	100	135	15	2-1/4"	X	TAS	4	SM	
PROJECTED OUT	7225 / 8225TL	65	65	15	2-1/4"	X	TAS	4	SM / LM	
PROJECTED IN	AA®900	70	90	15	2-5/8"	X	TAS	4	SM / LM	
PROJECTED OUT	AA®900	70	90	15	2-5/8"	X	TAS	4	SM / LM	
PROJECTED OUT	I3500	80	80	12	3-1/4"	X	TAS	4	LM	S-1648 / S-1649
fixed / project out										
FIXED / PROJECT OUT	7725 / 8225TL	100	130	15	2-1/4"	O/X	TAS	4	SM	
FIXED / PROJECT OUT	7725 / 8225TL	90	90	15	2-1/4"	O/X	TAS	4	LM	
FIXED / PROJECT OUT	AA®900				2-5/8"	O/X, X/O, X/X, O/O	TAS	4	SM / LM	
FIXED / PROJECT OUT	NX-3510I	100	100	15	3-1/4"	O/X	TAS	4	LM-D	
fixed										
FIXED	NX3800I	80	80	15	3-1/4"	O	TAS	4	LM-D	S-1542 / S-1543
FIXED	I3800	100	100	15	3-1/4"	O	TAS	4	LM-D	S-017 / S-018

Kawneer Company, Inc.
555 Guthridge Court
Norcross, GA 30092
770.449.5555 TEL

Traco
71 Progress Avenue
Cranberry Township, PA 16066
724.776.7000 TEL

kawneer.com

 **KAWNEER**
AN ALCOA COMPANY

 **TRACO**
A DIVISION OF KAWNEER