



PARABOND M-267

Premium Latex Carpet Seaming Adhesive

ENVIRONMENTAL/PERFORMANCE

- **Non-hazardous**
- **Fast drying**
- **Easy Spreading**

DESCRIPTION:

Parabond M-267 Premium Latex Carpet Seaming Adhesive is a natural latex adhesive designed for the application of carpet seaming and reinforcing tapes. It may also be used for replacing damaged or burned nap, sealing raw edges, strengthening worn backing and joining padding.

Parabond M-267 Premium Latex Carpet Seaming Adhesive is extremely fast drying, easy spreading, non-toxic, non-flammable and colorless when dry. Bonding strength increases with age and will not deteriorate after shampooing.

SURFACE PREPARATION:

Be sure all surfaces are clean, dry and free of dust, wax or any type of polish.

DIRECTIONS:

Shake container well before using.

BACK SEAMING:

1. Spread adhesive the length of the seam making sure you have even coverage.
2. Scrape excess adhesive toward center of the seam. Heavier ribbed carpet requires more adhesive.
3. Unroll seaming tape the length of the seam and tack both ends.
4. Smooth the entire length of the tape's surface to adhere tape and remove any wrinkles.
5. Allow to dry.

FACE SEAMING:

1. Unroll face seaming tape the length of the seam and apply adhesive.
2. Tape should be centered and tacked at both ends.

3. Smooth seam against tape.
4. Avoid too much pressure, as you do not want to force adhesive into carpet face.
5. Allow to dry.

CAUTION: This product may cause staining to hardwood, linoleum, etc. Immediate clean up is recommended.

COVERAGE:

One Quart provides Approx. 340 linear feet of 1/8" bead.

CLEAN UP:

Adhesive may be removed from carpet while still wet by repeated sponging with water and detergent. If adhesive has dried on the carpet, use PARABOND M-315 CLEANER/SOLVENT. Do not allow solvent to soak into the carpet; it will destroy the adhesive bond.

PHYSICAL PROPERTIES:

Weight/gallon (lbs)	8.0
Consistency	Off-white Liquid
Set up time	30 to 60 seconds with pressure
Freeze thaw stable @	Temperatures of 20°F or higher
Shelf Life	6 months

FOR MORE INFORMATION READ MATERIAL SAFETY DATA SHEET

KEEP OUT OF REACH OF CHILDREN

LIMITED WARRANTY:

Para-Chem's only obligation shall be to replace or pay for any adhesive proved defective when authorized in writing by the company. Beyond the purchase price of materials supplied by us, we assume no liability for any damages of any kind and the user accepts the product "as is" and without warranties, expressed or implied. The suitability of the product for an intended use shall be solely up to the user. 10-30-02

ISO 9001 Certified

Corporate Address: PO Box 127 • Simpsonville, SC 29681-0127 • 800-763-7272 • Fax: 864-228-1491
Manufacturing Facilities: Simpsonville, SC • Philadelphia, PA • Dalton, GA • Mansfield, TX • Adelanto, CA
www.parabond.com

MATERIAL SAFETY DATA SHEET

Page 1 of 3

Para-Chem[®], PO Box 127, Simpsonville, SC 29681

24-Hour Emergency Telephone: (864) 967-7691

SECTION 1. PRODUCT IDENTIFICATION

PRODUCT NAME: PARABOND M-267 Premium Latex Carpet Seaming Adhesive

CHEMICAL FAMILY: Water Base Adhesive

SECTION 2. HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS

<u>Chemical Name</u>	<u>CAS Number</u>	<u>% by Weight</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>
None				

SECTION 3. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Eyes, inhalation.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Latex allergies.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: May cause slight irritation.

SKIN CONTACT: May cause slight irritation

INGESTION: May cause discomfort to the digestive tract. Could cause blockage.

INHALATION: May cause mild irritation to nasal passages, throat, and lungs.

CHRONIC: None known.

CARCINOGENICITY: This product contains no ingredient above the OSHA minimum reporting threshold listed as a carcinogen listed by IARC, NTP, or OSHA.

SECTION 4. FIRST AID MEASURES

EYE CONTACT: Flush with water for 15 minutes. Contact a physician if irritation occurs.

SKIN CONTACT: Wash with soap and water.

INGESTION: Contact a physician immediately. Latex will coagulate in digestive tract.

INHALATION: Remove to fresh air.

SECTION 5. FIRE-FIGHTING MEASURES

FLASH POINT (°F): None.

FIRE-FIGHTING INSTRUCTIONS: Use protective clothing and self-contained breathing apparatus.

EXTINGUISHING MEDIA: Water fog, CO₂, dry chemical, and chemical foam.

DECOMPOSITION PRODUCTS: Dried material may produce CO, CO₂, NO_x, NH₃, and hydrocarbons.

SECTION 6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spill. Transfer to secure container(s) for recovery or disposal. Dispense sand, sawdust, or vermiculite and absorb residue. Collect and place in waste container. Wash area thoroughly with water.

MATERIAL SAFETY DATA SHEET

Page 2 of 3

SECTION 7. HANDLING AND STORAGE

HANDLING: Use good hygienic practices. Wash hands before eating, using washroom, or smoking. Keep out of the reach of children.

STORAGE: Store above 40° F. Keep container tightly sealed when not in use. Store in a cool, dry location away from heat and direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: Safety glasses or chemical splash goggles.

SKIN PROTECTION: Impervious synthetic rubber gloves.

RESPIRATORY PROTECTION: Not normally required with good ventilation. If used in confined locations, a NIOSH approved respirator with ammonia removal cartridge is recommended.

ENGINEERING CONTROLS: Normal room ventilation. Site specific mechanical ventilation (such as floor or ceiling fans) in confined locations or areas with poor ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (°F): 212

SPECIFIC GRAVITY (WATER = 1): 0.9

VAPOR PRESSURE: Same as water.

VAPOR DENSITY (air=1): Same as water.

% VOLATILE BY WEIGHT: 38.5

pH: 10.0

APPEARANCE AND ODOR: Creamy white liquid with slight ammonia odor.

GRAMS VOLATILE ORGANIC COMPOUNDS/LITER OF MATERIAL: 0 (Calculated)

SECTION 10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable.

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: None.

SECTION 11. TOXICOLOGICAL INFORMATION

No information available

SECTION 12. ECOLOGICAL INFORMATION

No information available.

MATERIAL SAFETY DATA SHEET

Page 3 of 3

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State and Local regulations.

SECTION 14. TRANSPORT INFORMATION

For domestic transportation purposes, this product is not designated as a hazardous material by the U.S. Department Of Transportation.

SECTION 15. REGULATORY INFORMATION

TSCA: The components of this product are listed on the TSCA inventory.

SARA TITLE III:

Section 311 and 312 Health and Physical Hazards:

Immediate	Delayed	Fire	Pressure	Reactivity
[]	[]	[]	[]	[]

Section 313: Contains no components at or above EPA reporting thresholds.

SECTION 16. OTHER INFORMATION

HMIS RATINGS: Health = 1 Flammability = 1
 Reactivity = 0 Personal Protective Equipment = B
 Hazard rating scale: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe

Para-Chem, Inc. believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.

DATE ISSUED: January 2, 2007 [Rev. 1]

CONTACT: R. W. Smith, Jr.