



BRICKFORM® Triple Seven Bond-Coat™

Reactive Primer

FEATURES:

- “Reactive Primer”
- Easy application
- Greatly enhances bonding to concrete
- Prevents the sub floor from absorbing moisture from overlay
- Interior or exterior use
- Great for priming all masonry surfaces: concrete, tile, terrazzo, brick, and overlays.
- Overlay may be applied on dry bond coat for up to two hours.

PRODUCT DESCRIPTION

BRICKFORM Triple Seven Bond Coat is a high-strength, premium, water-based, copolymer that provides added bond-strength, and is the perfect primer for BRICKFORM Stampable Overlay, Micro-Topping and SM Professional Grade. Because BRICKFORM Triple Seven Bond Coat re-emulsifies when wet, it is preferred over other acrylic primers for concrete resurfacing products. BRICKFORM Triple Seven Bond Coat can be used on any concrete surface.

SURFACE PREPARATION

Follow the recommended guidelines for Surface Preparation for the overlay product to be used. Brickform OL-60, SC-60, SM Professional, and Brickform Microtopping Technical Information Sheets are available at www.brickform.com.

APPLICATION

Brickform Triple Seven Bond Coat is applied to the concrete prior to placing a Brickform overlay product. Once the surface has been properly profiled and cleaned, allow the slab to dry completely. Apply Triple Seven Bond Coat full strength with a roller, pump up sprayer or low pressure airless sprayer. Allow the material to soak in to the slab and once the material tacks, the overlay material can be applied. Do not allow the Bond Coat to puddle. Do not apply the overlay if the Bond Coat is wet or if the material exhibits a whitish/blue appearance.

If the slab is very porous, two coats may be necessary.

The Bond Coat remains active for approximately 2 hours. Make sure the overlay material is applied during this time frame. If the material is allowed to sit for more than two hours, re-apply the Bond Coat.

STORAGE

Product should NOT be stored in temperatures above 90°F. Keep containers tightly sealed DO NOT allow product to freeze. DO NOT store for more than one year.

COVERAGE

Depending on the porosity and composition of the slab, Triple Seven Bond Coat will cover an average of 200 square feet/gallon.

TRIPLE SEVEN BOND COAT PROPERTIES

Coverage..... 200 square feet/gallon
 Drying time..... 30 - 60 minutes
 Leveling..... Excellent
 pH..... 8.0 - 9.0
 Recoat Very good
 Shelf life..... 1 year
 Specific gravity 1.04
 VOC 0

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assume all risks and liability.

MANUFACTURER

BRICKFORM, A Division of Solomon Colors, Inc.

ORDER SPECIFICATIONS

Triple Seven Bond Coat

Shipping Weight	Container Size	Item No.
40 lbs (18.9 L)	5 gallon	BC-007
10 Lbs (4.5 kg)	1 gallon	BC-0071