

ProForm® BRAND Texture Products

For new construction or remodeling, ProForm® BRAND offers a complete line of interior ceiling and wall textures. Textures provide an innovative time and money-saving option to ordinary painting. Textures are available in several light-reflecting finishes which provide a wide range of texturing possibilities on surfaces such as drywall, concrete, plaster, wood and metal. (Surfaces must be primed with a good quality primer recommended for the substrate.)

ProForm® Perfect Spray



Description

A decorative texture product with shredded polystyrene aggregate for fast spray application to interior ceiling surfaces. Available in fine, medium and coarse textures.

Applications

- Aggregate size available in fine, medium and coarse
- Interior ceilings that are formed of new, primed or previously painted gypsum wall-board or monolithic concrete or plaster

Features/Benefits

- Easy mixing, low fallout
- Works with standard spray equipment
- Greater whiteness, better hide and bold accent
- Provides innovative time/money savings option to ordinary painting

Packaging

Packaged in:
40 lb. (18.2 kg) bags
Approx. Coverage:
300-400 sq. ft.
(28-37 sq. m)/bag
Mixing:
3-4.5 gal. (13-17 L)
water/bag

ProForm® Perfect Spray II



Description

A decorative texture product with shredded polystyrene aggregate for fast spray application to interior ceiling surfaces.

Applications

- Commercial/residential interior ceilings

Features/Benefits

- Designed for fast spray application
- Hides minor surface defects and irregularities

Packaging

Packaged in:
40 lb. (18.2 kg) bags
Approx. Coverage:
300-400 sq. ft.
(28-37 sq. m)/bag
Mixing:
3-3.5 gal. (13-13.2 L)
water/bag

ProForm® Spray Quick®



Description

A white spray texture product recommended for interior ceilings that are formed of newly primed or previously painted gypsum boards or monolithic concrete or plaster. Available in fine, medium and coarse grades.

Applications

- Aggregate size available in fine, medium and coarse
- Provides a range of rugged ceiling textures

Features/Benefits

- Excellent coverage
- Dries to an "off-white" finish

Packaging

Packaged in:
40 lb. (18.2 kg) bags
Approx. Coverage:
300-400 sq. ft.
(28-37 sq. m)/bag
Mixing:
4-5 gal. (15-19 L)
water/bag

ProForm® Perfect Spray EM/HF



Description

A non-aggregated texture product used to create a wide range of wall and ceiling surfaces. When spraying walls, can be applied without overspray affecting ceiling. By adjusting mixture consistency and/or varying the pressure, creates an endless variety of textures – Spray Spatter, Spatter Knockdown and Orange Peel.

Applications


- Used for both walls and ceilings
- Wall surface should be finished with a coat of paint
- Concrete should be coated with an alkali-resistant primer/sealer prior to texturing

Features/Benefits

- Time and money-saving option to ordinary painted ceilings
- Textures available in several light-reflecting finishes
- Formulated for easy mixing and easy pumping
- Surface can be finished with a coat of paint

Packaging


Packaged in:
EM 50 lb. (22.7 kg) bags
HF 40 lb. (18.2 kg) bags
Approx. Coverage:
EM 500-1,500 sq. ft.
(46-139 sq. m)/bag
HF 400-1,200 sq. ft.
(37-111 sq. m)/bag
Mixing:
EM 4-5 gal. (15-19 L)
water/bag
HF 3.5-4.5 gal. (13-17 L)
water/bag




Perfect Spray Fine




Spray Quick Fine



**Perfect Spray EM/HF
– Spatter + Knockdown**




Perfect Spray Medium



Spray Quick Medium



**Perfect Spray EM/HF
– Orange Peel**




Perfect Spray Coarse



Spray Quick Coarse



**Perfect Spray EM/HF
– Spatter**



Perfect Spray II

Recommended Construction Practices

Surfaces, including joint-treated areas, must be smooth, clean and dry. First apply a coat of sealing primer. Allow primer to dry thoroughly, and maintain adequate drying conditions after application. Primer is to minimize sagging of gypsum wallboard and discoloration or difference in sheen on ceiling surface. Add dry texture to water. Use a piston pump or Moyno-type pump with a texture gun. Minimum 3/4" I.D. material hose. A hopper-type gun with adequate air supply is also suitable. Typical coverage is 8-10 sq. ft. per lb. for aggregated and 10-30 sq. ft. per lb. for nonaggregated textures. Mask appropriate areas before spraying and promptly remove overspray from unprotected surfaces afterward. Follow the instructions of the spray equipment manufacturer for adjusting controls and cleaning. If a second coat is desired, allow the first coat to dry thoroughly.

Note: Gypsum wallboard ceiling surfaces to be decorated with water-thinned spray texture shall be 1/2" or 5/8" thick and applied perpendicular to the framing. Framing shall not exceed 16" o.c. for Gold Bond[®] BRAND 1/2" Regular Wallboard and 24" o.c. for 1/2" High Strength[™] BRAND Ceiling Board and Gold Bond[®] BRAND 5/8" Wallboard.

CONCRETE:

Allow concrete to cure for at least 28 days. Clip protruding wire ends and spot with rust-inhibitive primer. Remove all form oil, grease and dirt, or any loose or water-soluble material. Grind down any form ridges, and level any remaining unevenness with ProForm[®] BRAND Sta-Smooth Joint Compound. Apply a coat of alkali-resistant sealing primer over the entire surface to be textured.

Spray Textures

| ProForm BRAND | Application | Aggregate | Bag Size | Mixing Water per Bag | Typical Coverage per Bag |
|-------------------------|------------------|----------------------|----------|----------------------|--------------------------|
| Perfect Spray | ceilings | shredded polystyrene | 40 lbs. | 3–4.5 gal. | 300–400 sq. ft. |
| Perfect Spray II | ceilings | shredded polystyrene | 40 lbs. | 3–3.5 gal. | 300–400 sq. ft. |
| Spray Quick | ceilings | perlite vermiculite | 40 lbs. | 4–5 gal. | 300–400 sq. ft. |
| Perfect Spray EM | walls & ceilings | none | 40 lbs. | 4–5 gal. | 500–1,500 sq. ft. |
| Perfect Spray HF | walls & ceilings | none | 40 lbs. | 3.5–4.5 gal. | 400–1,200 sq. ft. |

NOTE: Perfect Spray, Perfect Spray II, Spray Quick, Perfect Spray EM and Perfect Spray HF Burning Characteristics: Flame Spread–10, Smoke Developed–25

Corporate Headquarters

National Gypsum Company
2001 Rexford Road
Charlotte, NC 28211
Phone: (704) 365-7300
Web: nationalgypsum.com

Technical Information

Phone: (800) NATIONAL
(800) 628-4662
Fax: (800) FAX-NGC1
(800) 329-6421

National 
Gypsum[®]

Excellence Across The Board[®]