




TOILET WASTE LOCATION







TOILET ORIENTATION



(L)- ANGLED LEFT (L)- OFFSET LEFT





(R)- ANGLED RIGHT (R)- OFFSET RIGHT



(C)- CENTER

FIXTURE MOUNTING





LAVATORY BUBBLER SELECTION

STAINLESS STEEL






MACHINED



PENAL BUBBLER / FILLER PROVIDES A FLOW OF WATER FOR DRINKING AND FILLING THE BASIN.

(BP)- PENAL BUBBLER / FILLER



MACHINED STAINLESS STEEL

"CODE TYPE" PENAL BUBBLER / FILLER INCLUDES A MOUTH GUARD. MUST SPECIFY WHERE MOUTH GUARDS ARE REQUIRED BY LOCAL CODES.


(BC)- CODE BUBBLER / FILLER





HEMISPHERICAL
PENAL BUBBLER /
FILLER PROVIDES A
FLOW OF WATER FOR
DRINKING AND FILLING
THE BASIN. DESIGN IS
LIGATURE-RESISTANT.

(BPH)- LIGATURE-RESISTANT BUBBLER / FILLER



MACHINED STAINLESS STEEL

LAVATORY FILLER PROVIDES A FLOW OF WATER TO THE LAVATORY BASIN ONLY.

(FL)- PENAL LAV. FILLER

MACHINED STAINLESS STEEL



HEMISPHERICAL LAVATORY FILLER PROVIDES A FLOW OF WATER TO THE LAVATORY BASIN ONLY. DESIGN IS LIGATURE-RESISTANT.

(FLH)- LIGATURE-RESISTANT LAV. FILLER



MACHINED STAINLESS STEEL

DECK MOUNTED BUBBLER / FILLER PROVIDES A FLOW OF WATER FOR DRINKING AND FILLING THE BASIN.

(DMB)- DECK MOUNTED BUBBLER /

MACHINED STAINLESS STEEL




HEMISPHERICAL DECK MOUNTED BUBBLER/ FILLER PROVIDES A FLOW OF WATER FOR DRINKING AND FILLING THE BASIN. DESIGN IS LIGATURE-RESISTANT.

(DMBH)- LIGATURE-RESISTANT DECK MOUNTED BUBBLER / FILLER


(317) 875-0830 • Fax: (317) 875-0837 • (800) 428-4065

LAVATORY WASTE







(EB)- ELBOW WASTE (1-1/2" F.I.P.)




(PT)- INTEGRAL P-TRAP (1-1/2" F.I.P.)




(LWE)- LAVATORY WASTE EXTENSION (1-1/2" F.I.P.)




(CW1)- COMBINED WASTE W/O CLEANOUT (CHECK CODES FOR ACCEPTANCE)




(CW2)- COMBINED WASTE W/ CLEANOUT (1-1/2" F.I.P.) (CHECK CODES FOR ACCEPTANCE)




(CW2) FOR "FA"- COMBINED WASTE W/ "FA" CLEANOUT (1-1/2" F.I.P.) (CHECK CODES FOR ACCEPTANCE)




(OV)- LAVATORY OVERFLOW




(LW1)- BRASS THRU-WALL EXTENSION P-TRAP (FOR USE W/ (EB) ELBOW WASTE)



(SLOW)- SLOW DRAIN



(LW2)- BRASS THRU-WALL EXTENSION P-TRAP (FOR USE W/ (PT) INTEGRAL 'P'-TRAP)




(317) 875-0830 • Fax: (317) 875-0837 • (800) 428-4065




TOILET WASTE






THE TOILET WASTE EXTENSION EXTENDS THE STAINLESS STEEL WASTE TUBE OUT THE BACK OF THE FIXTURE ALLOWING FOR A NOHUB TYPE CONNECTION. SPECIAL NO-HUB COUPLING IS REQUIRED. SPECIFY CONNECTING PIPE SIZE AND TYPE.

(TWE)- TOILET WASTE EXTENSION



TOILET WASTE CONNECTION, SUPPLIED COMPLETE WITH Ø5-1/4" NEOPRENE GASKET, 5/16" ANCHOR STUDS AND 4" x 4" FLOOR FLANGE.


(TW4) FLOOR OUTLET WASTE CONNECTION




THE PINNED CLEAN-OUT PLUG IS USED TO STOP LARGE OBJECTS FROM ENTERING THE BUILDING'S MAIN WASTE SYSTEM.

3" PVC OR 4" PVC CLEAN-OUT PLUGS ARE STANDARD. BRASS CLEAN-OUT PLUGS ARE AVAILABLE UPON REQUEST. SPECIFY "PCB" FOR BRASS.

(PC__)- PINNED CLEAN-OUT PLUG




(COH__) CLEAN-OUT HOOK



FABRICATED FROM 3" OR 4" GALVANIZED STEEL PIPE.

INCLUDES (2) SHARPENED 1/4" STAINLESS STEEL RODS STRATEGICALLY LOCATED FOR CATCHING LARGE DEBRIS ITEMS IMMEDIATELY BEHIND INDIVIDUAL PLUMBING FIXTURES RATHER THAN FURTHER DOWN THE WASTE LINE.


(NLY__) NALLYATOR WASTE LINE DEVICE



(TW3)- NO-HUB WASTE W/3" CLEAN-OUT




(TW5)- NO-HUB WASTE W/ 4" CLEAN-OUT



(WO3) TOILET 'P'-TRAP (3.5 GPF ONLY)



(GWC)- GASKETED WASTE CONNECTION (WALL OUTLET SHOWN)



(TWC__)- TOILET WASTE COUPLING




visit our website at www.willoughby-ind.com 5105 West 78th Street ● Indianapolis, IN. 46268 (317) 875-0830 ● Fax: (317) 875-0837 ● (800) 428-4065

\$1-32 © Rev. 1/2016

OTHER OPTIONS



WILLOUGHBY



THE TOILET OVERFLOW PREVENTER IS RECOMMENDED FOR FACILITIES WITH HIGH VANDALISM. (T4) IS NORMALLY USED IN CONJUNCTION WITH A BACK SUPPLY TOILET OR COMBINATION UNIT WHERE AN ACCESSIBLE PIPE CHASE IS PROVIDED


(T4)- MANUAL RESET TOP FOUR OVERFLOW PREVENTER (REQUIRES HYDRAULIC FLUSH VALVE)



ELONGATED PLASTIC SEAT IS OF SANITARY, OPEN FRONT DESIGN, NOT RECOMMENDED IN MAXIMUM SECURITY AREAS

(AVAILABLE IN WHITE)

(HS)- HINGED PLASTIC SEAT



TOOTHBRUSH HOLDER(S) CAN BE MOUNTED TO EITHER SIDE OR BOTH SIDES OF THE FIXTURE BACKSPLASH, THE TOOTHBRUSH HOLDER IS FASTENED TO THE FIXTURE CABINET.

(MUST SPECIFY LOCATION)


(TB1__)- SINGLE TOOTHBRUSH HOLDER (TB2__)- DUAL TOOTHBRUSH HOLDER



JACKSON CONTROL OR EQUIVALENT 24V 40A TRANSFORMER. FOOT MOUNT END COVERS, VERTICAL W/ 1/2" THREADED CONDUIT HUBS & LOCK NUTS ON BOTH EXITS.

TRANSFORMER TO BE LABELED WITH "UL" AND "CSA" CERTIFICATION MARKS.


(TF24)- TRANSFORMER, 110V TO 24V



A SERIES OF 1/4" HOLES PUNCHED ON 1/2" CENTERS PROVIDES AN ECONOMICAL MEANS OF PROVIDING A RETURN AIR SOURCE THROUGH THE FIXTURE AND WALL OPENING. (DUCT WORK AND DUCT FLANGES BY OTHERS).


(MUST SPECIFY LOCATION AND FREE AREA REQUIREMENTS.)

(VG)- VENTILATION GRILLE



THE TOILET OVERFLOW PREVENTER IS RECOMMENDED FOR FACILITIES WITH HIGH VANDALISM. (T4A) IS NORMALLY USED IN CONJUNCTION WITH A BACK SUPPLY TOILET OR COMBINATION UNIT WHERE AN ACCESSIBLE PIPE CHASE IS PROVIDED

(T4A)- AUTO RESET TOP FOUR OVERFLOW PREVENTER (REQUIRES HYDRAULIC FLUSH VALVE)



DESIGNED TO ACCOMMODATE A STANDARD TISSUE ROLL. THE TISSUE HOLDER IS WELDED INTO THE CABINET, GROUND SMOOTH AND POLISHED.

(MUST SPECIFY LOCATION)

(RTH)- RECESSED TISSUE HOLDER



THIS PRESSURE ACTIVATED RELEASE TOWEL HOOK WILL SUPPORT LIGHT CLOTHING & TOWEL LOADS, HOWEVER, EXCESSIVE LOADS PLACED ON THE HOOK WILL CAUSE IT TO RELEASE DOWNWARD.


(MUST SPECIFY LOCATION)

(TH1__)- SINGLE TOWEL HOOK (TH2__)- DUAL TOWEL HOOK



TOILET SEAT TOP IS POLISHED TO A #7 MIRROR FINISH.

(HPS)- HIGH POLISH SEAT



CONSTRUCTED OF 18 GAUGE GALVANIZED STEEL.

METAL WALL TEMPLATES PROVIDE FOR FIXTURE ROUGH-IN CUT-OUTS IN A STEEL WALL. THE TEMPLATE HAS INTEGRAL LAYOUT PATTERNS FOR CUTTING OR DRILLING WALL OPENINGS.

(MT)- WALL TEMPLATE



visit our website at www.willoughby-ind.com 5105 West 78th Street ● Indianapolis, IN. 46268 (317) 875-0830 ● Fax: (317) 875-0837 ● (800) 428-4065

© Rev. 5/2016 \$1-33

<u>OTHER OPTIONS (CONTINUED)</u>






CONSTRUCTED OF 20 GA. GALVANIZED STEEL, WALL SLEEVES PROVIDE FIXTURE PLUMBING ROUGH-IN OPENINGS IN BLOCK/POURED CONCRETE WALLS, BECOMING A PERMANENT PART OF THE WALL


THE Ø1/2" STEEL RODS WELDED TO THE FRAME PROVIDE RIGIDITY AND HINDER ESCAPE INTO THE CHASE SHOULD THE FIXTURE BE REMOVED.

(SLEEVE BRACING IS REQUIRED DURING WALL CONSTRUCTION, BY OTHERS. MUST SPECIFY WALL THICKNESS AND TYPE WHEN ORDERING SLEEVE)

(WS)- WALL SLEEVE



(SK)- LIGATURE-RESISTANT TOILET SKIRT



FLUSH VALVE TAILPIECES ARE FURNISHED STANDARD WITH SLIP JOINT FIXTURE CONNECTIONS . STANDARD SLIP JOINT CONNECTIONS WILL WORK FOR WALL THICKNESSES UP TO 2", BEYOND WHICH THE CONNECTION BECOMES MORE DIFFICULT TO MAKE

WILLOUGHBY RECOMMENDS THE USE OF A THRU-THE-WALL FLUSHING CONNECTION, ALLOWING FOR THE CONNECTION TO BE MADE IN THE CHASE.

(FVT)- FLUSH VALVE THROUGH WALL CONNECTION



(ISH)- INTEGRAL SHELF



PROVIDES WATER SUPPLY CONTROL FOR FLUSHING WATER CLOSETS. DELANY, SLOAN, AND ZURN FLUSH VALVES ARE COMPATIBLE WITH WILLOUGHBY UNITS.

FLUSH VALVES ARE AVAILABLE IN 3.5 GPF, 1.6 GPF, AND 1.28 GPF.

(SEE S11-SUPPLEMENTAL INFORMATION)

(FV)- FLUSH VALVE




PROVIDES WATER SUPPLY CONTROL FOR FLUSHING WATER CLOSETS. DELANY, SLOAN, AND ZURN FLUSH VALVES ARE COMPATIBLE WITH WILLOUGHBY UNITS.

FLUSH VALVES ARE AVAILABLE IN 3.5 GPF, 1.6 GPF, AND 1.28 GPF.

(SEE S11-SUPPLEMENTAL INFORMATION)


(EFV)- ELECTRONIC FLUSH VALVE (FOR USE W/ WILLOUGHBY ELECTRONIC CONTROLS)



1-1/2" MALE I.P.S. FLUSHING INLET EXTENSION, EXTENDS FLUSH VALVE CONNECTION BEYOND BACK OF FIXTURE.

MUST SPECIFY LENGTH.

(TFE)- TOILET FLUSH EXTENSION



THIS OPTION PROVIDES A STAINLESS STEEL SHIPPING COVER FOR TOILET BOWLS.

COVERS ARE DESIGNED TO LIMIT POSSIBLE INSERTION OF FOREIGN MATERIAL INTO THE FIXTURE PRIOR TO FACILITY STARTUP.


(TSC)- TOILET SHIPPING COVER

visit our website at www.willoughby-ind.com 5105 West 78th Street ● Indianapolis, IN. 46268 (317) 875-0830 ● Fax: (317) 875-0837 ● (800) 428-4065




WILLOUGHBY


OTHER OPTIONS (CONTINUED)



(GBC)- GRAB BAR CLOSURE PLATE



(LVCP)- LAVATORY CLOSURE PLATE



(LGB)- LESS GRAB BAR (ON (GB)-STANDARD COMBI)



PLACEMENT DIAGRAMS



