



WORLD CLASS PERFORMANCE SINCE 1930

The Path to Beautiful Decorative Concrete



Kemiko Products conform to LEED guidelines

◆ Kemiko Stone Tone Stain

◆ Kemiko Stone Tone Buff On Wax II

◆ Kemiko Stone Tone Sealer II
Low Viscosity Acrylic Urethane

◆ Kemiko Easy Shine Liquid Wax

◆ Kemiko Neutra Clean
Industrial Strength Cleaner

◆ Kemiko/Sta-Crete 1202
100% Solids Epoxy

◆ Kemiko/Sta-Crete 1600
Water Extended Epoxy Coating

◆ Kemiko/Sta-Crete 2700
Waterborne Aliphatic Polyurethane

◆ Kemiko/Sta-Crete 3300
100% Solids Polyaspartic

◆ Kemiko/Sta-Crete 3500
100% Solids Pigmented Epoxy

◆ Kemiko/Sta-Crete 3700
Water Extended High Gloss
Epoxy Coating

◆ Kemiko/Sta-Crete 3800
Water Extended, Quick Dry,
High Gloss Epoxy



www.kemiko.com

KEMIKO® CONCRETE PRODUCTS



KEMIKO Stone Tone Concrete Stain

Cola Stain

Reddish Brown Resembling Old Leather

Malay Tan Stain

Buckskin Suede Tone with Carmel Marbling

Aqua Blue Stain

Soft Blue Patina with Undertones of Green

Black Stain

Tortoise Shell Black with Brown Marbling

Golden Wheat Stain

Amber Hued Undertones

English Red Stain

Terra Cotta with Rust and Soft Brown Hues

Vintage Umber Stain

Rich Earthy Brown

Green Lawn Stain

Soft Grey Green Resembling Aged Italian Marble

KEMIKO Stone Tone Stain

Transforms an ordinary concrete slab into a luxurious floor that resembles marble or glazed stone. When concrete is scored and stained, Kemiko creates the appearance of expensive flooring at a fraction of the cost.

Whether working with a neo-classic, Southwestern, eclectic, or traditional décor, Stone Tone Stain adapts to enhance any setting.

Description

KEMIKO Stone Tone Concrete Stain is an acid base, single component product that provides a decorative, low maintenance floor finish and is 0-VOC. This class product contains special wetting agents, which chemically combine metallic ions with the particles in the concrete to form colored oxides. Kemiko Stone Tone Stain is the perfect choice for interior and exterior projects.

Applications

Kemiko Stone Tone Stain is applied to properly prepared concrete and cement/plaster material that contains sufficient cement material for color reaction. Typical applications include homes, driveways, patios, tilt walls, restaurants, shopping malls, and other interior/exterior applications where quality, cost-effective color enhanced concrete is desired.

KEMIKO Neutra Clean

Description

KEMIKO Neutra Clean is an industrial strength, high performance water base sodium metasilicate cleaner for the preparation of bare concrete and coated substrates. It has a pleasant citrus odor and does not contain any hazardous solvents.

Applications

KEMIKO Neutra Clean is typically applied to concrete substrates to remove deleterious matter such as grease, grime, soil, wall plaster and other construction related residue. Typical applications include commercial kitchens, grocery stores, restaurants, showroom floors, walkways, and many other interior/exterior surfaces requiring cleaning.

KEMIKO Stone Tone Wax II

Description

KEMIKO Stone Tone Wax II is formulated to produce a low sheen finish with good protection and durability. Designed for interior use over Kemiko Stone Tone Stains, pigmented colored concrete, tile, brick, or any masonry surface.

Applications

KEMIKO Stone Tone Wax II is ideal for interior residential and light commercial projects such as offices, art galleries, and showrooms.





KEMIKO Stone Tone Sealer II

Description

KEMIKO Stone Tone Sealer II is a water-borne, water viscosity, single component, superior coalescing acrylic urethane polymer product that offers ultra-low VOC, is user friendly, stain resistant, and cures to a hard resilient finish. Kemiko Stone Tone Sealer II is supplied in clear gloss and clear natural looking flat to satin sheen, and is non-yellowing when subjected to exterior atmospheric exposure.

Applications

KEMIKO Stone Tone Sealer II is applied to properly prepared concrete, plaster, wood, and metals. It is used as a resilient protective finish coat over faux finishes, Kemiko Acid Stains, and other topcoats for added UV resistance, abrasion resistance, and washability.

Typical applications include residential and commercial concrete floors, and other floor surfaces requiring additional protection. Kemiko Stone Tone Sealer II is an excellent replacement product for high VOC lacquers, acrylics and varnishes and quickly cures to a hard resilient film with excellent properties.

KEMIKO Easy Shine Liquid Wax

Description

KEMIKO Easy Shine is a water-based acrylic polymer interior floor polish. It is a one component, room temperature cure, mop-on floor polish. Easy Shine has good durability and is easy to clean.

Applications

KEMIKO Easy Shine is a maintenance top-coat applied over properly cured Kemiko Stone Tone Sealer II, or Kemiko Poly Finish. Typical applications include commercial and residential concrete floors requiring additional protection.

KEMIKO Sta-Natural Sealer

Description

KEMIKO Sta-Natural Sealer is a 0-VOC, user friendly, waterborne silane/siloxane emulsion for sealing Kemiko Stone Tone stained concrete and other cementitious substrates. Sta-Natural Sealer is a water viscosity, single component product that is designed to repel water, reduce efflorescence and frost damage, allow substrate to breathe, has very little or no odor, contains no solvents, and preserves stained concrete color. Sta-Natural Sealer is resistant to UV and high alkalinity exposure.

Applications

KEMIKO Sta-Natural Sealer is applied to properly stained or bare concrete, new and existing stucco finishes, fired clay brick, and many other cementitious mortars. Typical applications include commercial and residential driveways, walkways, pool decks, stamped and stained concrete, new architectural poured-in-place and pre-cast concrete, as well as many other horizontal and vertical above grade exterior surfaces requiring additional protection. Excellent replacement product for high VOC solvent base water repellents and sealers, with excellent wetting properties.

KEMIKO/Sta-Crete 1202 100% Solids Epoxy

Description

KEMIKO/Sta-Crete 1202 is a 100% solids, low viscosity, 0-VOC, water clear epoxy coating that has excellent chemical resistance, is designed to be used with color quartz and selected aggregate, is user friendly and cures to a bluish free resilient high gloss film. KEMIKO/Sta-Crete 1202 is USDA acceptable in food processing facilities cures overnight and is available in two speeds.

Applications

KEMIKO/Sta-Crete 1202 may be applied to properly prepared concrete floors subject to continuous foot traffic, showroom floors, warehouse floors, food & chemical processing facilities, hospitals kitchens, breweries, laboratories, gymnasiums and many other applications that require a high gloss resilient floor finish. The low viscosity mixture allows easy aggregate filling for slurry applications or aggregate broadcast systems for increased compressive strength and high impact service.

LOCATION	APPEARANCE PATHS	STEP 1 FLOOR PREPARATION	STEP 2 DECORATION	STEP 3 RESIDUE REMOVAL	STEP 4 PROTECTION COAT	STEP 5 TOP COAT	STEP 6 WAX REMOVAL
INTERIOR	RICH LUSTER PATH	NEUTRA-CLEAN	KEMIKO STAIN	NEUTRA-CLEAN	BUFF-ON WAX		
INTERIOR	GLOSSY PATH	NEUTRA-CLEAN	KEMIKO STAIN	NEUTRA-CLEAN	STONE TONE SEALER II	EASY SHINE LIQUID	EASY STRIP
**INTERIOR	COMMERCIAL PATH	NEUTRA-CLEAN	KEMIKO STAIN	NEUTRA-CLEAN	EPOXY FINISH	EASY SHINE LIQUID	EASY STRIP
EXTERIOR	NATURAL FINISH	NEUTRA-CLEAN	KEMIKO STAIN	NEUTRA-CLEAN	STA-NATURAL		
EXTERIOR	GLOSS OR MATTE	NEUTRA-CLEAN	KEMIKO STAIN	NEUTRA-CLEAN	STONE TONE SEALER II		
**EXTERIOR	COMMERCIAL PATH	NEUTRA-CLEAN	KEMIKO STAIN	NEUTRA-CLEAN	POLY FINISH		

**Path to be followed only by professional applicators.

KEMIKO/Sta-Crete Standard Colors

Light Gray

Gray

Diego Blue

Navajo White

Beige

Bernard Tan

Whisper Gray

Colors are approximations. Results may vary.

KEMIKO/Sta-Crete 1600 Water Extended Epoxy Coating

Description

KEMIKO/Sta-Crete 1600 is a quality abrasion resistant, amine cured, water extended epoxy coating that offers low-VOC, has excellent adhesion, surface tolerance, low odor, and is designed to be used as a thin resilient primer/finish. KEMIKO/Sta-Crete 1600 has over 20 years successful case history and is USDA acceptable in food processing facilities, cures overnight and is available in various colors.

Applications

KEMIKO/Sta-Crete 1600 is applied to properly prepared cement and steel substrates subject to abrasion service, warehouse floors, garages, architectural applications, food and chemical processing facilities, hospitals and other applications requiring a cost-effective surface tolerant general maintenance primer/finish.

KEMIKO/Sta-Crete 2700 Waterborne Aliphatic Polyurethane Sealer

Description

KEMIKO/Sta-Crete 2700 Aliphatic Polyurethane is a waterborne, universal, high solids, two component product that offers 0-VOC, UV resistance, good chemical resistance, excellent abrasion resistance, is user friendly, and cures to a very durable finish. KEMIKO/Sta-Crete 2700 is available in standard colors as well as clear. When subjected to UV exposure, KEMIKO/Sta-Crete 2700 has a temporary amber cast.

Applications

KEMIKO/Sta-Crete 2700 may be applied to properly prepared concrete, plaster, wood, FRP, GFRC, and metals. It is utilized as a resilient protective finish coat over KEMIKO/Sta-Crete water base epoxies and KEMIKO'S Acrylic Urethane for optimum corrosion resistance. Typical applications include hospital walls and floors, commercial concrete floors, facades, steel and concrete storage tank exteriors, steel and concrete bridges, pump equipment, and many other surfaces requiring abrasion resistance, graffiti resistance, color retention, and chemical resistance.

KEMIKO/Sta-Crete 3300 100% Solids Polyaspartic

Description

KEMIKO/Sta-Crete 3300 is a 100% solids two component polyaspartic that exhibits excellent adhesion, UV resistance, abrasion resistance, chemical resistance, is 0-VOC and has rapid setting properties. It may be used as a decorative or industrial environment basecoat and topcoat for exterior concrete and carbon steel substrates. KEMIKO/Sta-Crete 3300 is low odor and utilizes the best available 100% solids polyaspartic technology for atmospheric and chemical exposure.

Applications

KEMIKO/Sta-Crete 3300 is applied to properly prepared and prime coated concrete and steel for use in food processing plants, water treatment facilities, warehouse and showroom floors, airport maintenance facilities, parking deck garages, chemical containment, exterior concrete and steel tanks, pipelines and many other service areas which require a resilient, chemical resistant, quick curing protective coating. It may also be used for incidental food contact applications.

KEMIKO/Sta-Crete 3500 100% Solids Pigmented Epoxy

Description

KEMIKO/Sta-Crete 3500 100% Solids Pigmented Epoxy is a two component, abrasion resistant epoxy coating that offers 0-VOC, excellent adhesion to steel and concrete, is user friendly and cures to a very hard resilient high-gloss film. It is non-blushing in high humidity, cures overnight and is available in many colors.

Applications

KEMIKO/Sta-Crete 3500 100% Solids Pigmented Epoxy may be applied to properly prepared concrete, metals and utilized as a resilient protective coating for chemical containment, abrasion resistance and as a complete 0-VOC exterior coating system when coated with KEMIKO/Sta-Crete 2700 Aliphatic Urethane for optimum color and gloss retention. Typical applications include hospital and food processing floors, petrochemical & chemical secondary containment, warehouse flooring, and showroom floors.

KEMIKO/Sta-Crete 3700 Water Extended High Gloss Epoxy Coating

Description

KEMIKO/Sta-Crete 3700 is a high gloss, quick dry amine cured, water extended epoxy coating that offers excellent adhesion, abrasion resistance and low odor. It is designed to be used as a thin resilient primer finish. KEMIKO/Sta-Crete 3700 can be applied on concrete walls, steel, wood, and plaster surfaces. It has been used successfully for over 10 years, is USDA acceptable in food processing facilities, is recoatable in 1-2 hours, and is available in various colors, as well as clear.

Applications

KEMIKO/Sta-Crete 3700 is applied to properly prepared concrete and steel substrates subject to abrasion service, architectural applications, food and chemical processing facilities, hospitals, water and wastewater treatment facilities, and many other applications that require a cost-effective and surface tolerant primer/finish.

KEMIKO/Sta-Crete 3800 Water Extended Quick Dry High Gloss Epoxy Coating

Description

KEMIKO/Sta-Crete 3800 is a high gloss, ultra low VOC, quick dry, water extended epoxy coating that offers excellent adhesion and low odor. It is designed to be used as a thin film resilient primer finish. It is recoatable in 1-2 hours and is available in clear and various colors.

Applications

KEMIKO/Sta-Crete 3800 may be applied to properly prepared cement and steel substrates subject to abrasion service, architectural applications, food and chemical processing facilities, hospitals, water and wastewater treatment facilities and many other applications that require a cost-effective surface tolerant general maintenance primer/finish.

Contact us for your nearest Kemiko Stain Dealer

Phone: 800-875-4596 • Email: epmar@quakerchem.com • www.kemiko.com • www.epmar.com