



catalog of appliances

Now you can offer a choice between a kitchen designed with the latest in cooking innovations and a modern kitchen with true local flavor.

Your customers can experience the right combination of high style and performance with GE Profile™ appliances. Clean lines, bold curves and custom finishes make a dramatic statement, creating a beautiful kitchen to enjoy now and for many years to come.

Or they can create an enchanting little spot with fantastic food and charming atmosphere with the new GE Café™ kitchen. With its smooth stainless steel and innovative cooking conveniences, it transforms any kitchen into a corner café. For more information on GE Profile, GE Café and GE® appliances, visit geappliances.com.



Profile™

Café™



GE Profile™, GE Café™ and GE® refrigerators



CSCP5UGX

GE Café
25.4 cu. ft.
refrigerator

- Counter-depth configuration
- GE Café stainless steel handles with stainless sides
- ClimateKeeper²™ system
- External controls with actual-temperature display and UltraFlow₁₀₀
- ExpressChill™
- Slide 'n Store™ freezer baskets
- Quick Ice™ setting
- TurboCool™ setting
- Integrated Ice™ system



GSS25WST

GE 25.4 cu. ft.
refrigerator



- External controls with actual-temperature display and UltraFlow₆₄
- Integrated shelf support system
- Adjustable-humidity crisper drawer
- Adjustable-temperature deli drawer
- Snack drawer



PFSS2MIY

GE Profile
22.2 cu. ft.
French-door
refrigerator



- Stainless steel doors with top and bottom bevels
- Internal water dispenser with GE water filtration
- ClimateKeeper system
- Factory-installed icemaker with water filtration system
- BrightSpace™ interior with GE Reveal® lighting
- Freshness Center™
- Multi-level Slide 'n Store system
- QuickSpace™ shelf
- TurboCool setting



GTH21KCX

GE 21.0 cu. ft.
refrigerator



GTS21KCX

Similar to the
GTH21KCX
except not
ENERGY STAR®
qualified.

- ENERGY STAR qualified
- Adjustable spill-resistant glass shelves
- Spillproof freezer floor
- Factory-installed icemaker
- Adjustable-humidity crisper drawers
- Snack drawer
- Upfront temperature controls
- Wire freezer shelf



PT956

GE Profile 30" double oven

- Glass touch controls
- PreciseAir™ convection system (upper oven only)
- Flat back convection (upper oven only)
- Convection bake/roast (upper oven only)
- Hidden bake oven interior
- Self-clean, heavy-duty oven racks



PT925

GE Profile 30" single-double wall oven

- Two ovens in one space
- EasyReach oven
- Super-large 5.0 cu. ft. oven capacity
- Self-clean oven (upper and lower oven)
- PreciseAir convection system (lower)
- In-the-door ShadowTouch controls
- Pizza mode
- Slow cook mode
- Self-clean heavy-duty oven racks



PT916

GE Profile 30" single oven

- Glass touch controls
- PreciseAir convection system
- Flat back convection
- Convection bake/roast
- Hidden bake oven interior
- Self-clean, heavy-duty oven racks



JTP30

GE 30" single oven

- Self-clean oven
- Super-large oven capacity
- Electronic oven controls
- TrueTemp™ oven system
- Hidden bake oven interior



GE Profile,[™] GE Café[™] and GE[®] free-standing ranges



PB975
GE Profile
30" double
electric
oven range

- Double oven 6.6 cu. ft total oven capacity
- PreciseAir[™] convection system
- Convection Cook
- 12"/9"/6" tri-ring element
- Bridge element
- Warming zone
- Pizza mode
- Slow cook mode



JBP66
GE 30"
electric range

- Self-clean oven
- Super-large 5.3 cu. ft. oven capacity
- TrueTemp[™] oven system
- 9"/12" dual element
- Ceramic glass cooktop
- QuickSet oven controls
- Six-pass bake element
- Big hearth window



CGS980
GE Café
30" gas range

- PreciseAir convection system
- Super-large 5.0 cu. ft. oven capacity
- Baking drawer
- Self-clean oven
- Deep-recessed stainless steel cooktop
- 18,000 BTU dual-flame stacked burner
- Center oval burner with non-stick griddle
- Gas cooktop with oven lock-out



PGB908
GE Profile 30"
gas range

- Self-clean oven
- Super-large, 5.0 cu. ft. oven capacity
- Deep-recessed cooktop
- PowerBoil[™] 17,000 BTU burner
- Warming drawer
- Center oval burner with non-stick griddle



PP975

GE Profile 36" electronic touch control cooktop

- Electronic touch controls
- Control lock capability
- Ribbon heating elements
- 12"/9"/6" tri-ring element
- 5"/8" PowerBoil element
- 5"/8" dual element
- Warming zone
- Full stainless steel frame on stainless steel model
- Upright controls



PP950

GE Profile 30" electronic touch control cooktop

- Electronic touch controls
- Control lock capability
- Ribbon heating elements
- 12"/9"/6" tri-ring element
- 5"/8" PowerBoil element



JGP970

GE Profile 36" gas-on-glass cooktop

- Gas-on-glass cooktop
- Sealed cooktop burners
- PowerBoil 15,000 BTU burner
- Precise Simmer burner
- Continuous grates
- Dishwasher-safe grates and knobs
- Control lock capability
- Heavy-duty knobs on stainless steel model



JGP940

GE Profile 30" gas-on-glass cooktop

- Gas-on-glass cooktop
- Sealed cooktop burners
- PowerBoil 15,000 BTU burner
- Precise Simmer burner
- Continuous grates
- Dishwasher-safe grates and knobs
- Control lock capability
- Heavy-duty knobs on stainless steel model



GE Profile™ ventilation products



JV966

GE Profile 36" designer hood

- 600 CFM blower
- Four-speed fan control
- Vertical exhaust
- Halogen cooktop light
- Nightlight
- Removable grease filter
- Optional chimney cover available at additional cost



JV666/665

GE Profile 36" high-performance hood

- Vented
- Vertical and rear exhaust
- 4-speed fan control
- Halogen cooktop light
- Removable grease filter
- Round or rectangular ducting



JV536/535

GE Profile 30" high-performance hood

- Convertible venting
- Vertical or rear exhaust
- Variable two-speed fan control
- Halogen light
- Removable grease filter
- Round or rectangular ducting

GE Profile Advantium® ovens



PSB2201/2200

GE Profile Advantium 240V 30" wall oven

- Speedcook technology—cooks up to 8 times faster than a conventional oven
- 4 ovens in 1: Speedcook, True European Convection, Warming/Proofing, Sensor Microwave
- Optimizes cook time for consistent results
- Saves valuable time by eliminating preheating
- 16" turntable
- Over 175 preprogrammed recipes
- Full-width oven rack for multilevel cooking
- Includes speedcooking grill tray for preparing meats



SCA1001/1000

GE Profile Advantium 120V above-the-cooktop oven

- Speedcook technology—cooks up to 4 times faster than a conventional oven
- 4 ovens in 1: Speedcook, Traditional oven, Warming and Sensor Microwave
- Optimizes cook time for consistent results
- Saves valuable time by eliminating preheating
- Over 100 preprogrammed recipes
- Allows up to 30 customized recipes to be saved



JVM3670

GE Profile Spacemaker® 1.8 cu. ft. 36" sensor oven

- 36" width installation
- 1.8 cu. ft. capacity, 1100 watts[†]
- CircuWave™ 1100 cooking system
- Sensor cooking controls
- Active hidden vent
- 1-lb. Quick Defrost
- 14-1/4" recessed turntable



CVM2072

GE Café 2.0 cu. ft. sensor oven

- 2.0 cu. ft. capacity, 1100 watts[†]
- Dual distribution cooking system
- EasyGuide™ menu system
- Soften, Melt and 1-lb. Quick Defrost features
- Full-width active hidden vent
- 14-1/4" recessed turntable with On/Off
- Four-speed*** 315-CFM venting system
- Removable oven rack



PVM1870/ PNM1871^{††}

GE Profile Spacemaker 1.8 cu. ft. sensor oven

- 1.8 cu. ft. capacity, 1100 watts[†]
- CircuWave 1100 cooking system
- Sensor cooking controls
- Melt feature
- Full-width active hidden vent
- 14-1/4" recessed turntable with On/Off



PEB2060

GE Profile 2.0 cu. ft. sensor oven

- 2.0 cu. ft. capacity, 1200 watts[†]
- Sensor cooking controls
- Optional built-in trim kit**
- Auto and Time Defrost
- Extra-large 16" turntable
- Instant On controls
- Control lockout



*ADA compliant based on Uniform Federal Accessibility Standards
 **Optional trim kits available in 27" and 30" configurations at an additional cost
 ***Includes boost option
[†]IEC-705 test procedure
^{††}Non-vented model

GE Café™, GE Profile™ and GE® dishwashers



CDWT980R

GE Café stainless interior dishwasher with hidden controls

- PureClean wash system with 5-stage filtration
- SmartDispense™ technology*
- DeepClean™ Cycle with Steam Prewash
- Eclipse black nylon deep-tiered four position adjustable upper rack
- Nylon coated utility shelves with StemSafe™ in upper rack
- 5 cycles/5 options
- Fan-assist dry



PDWT480R

GE Profile stainless interior dishwasher with hidden controls

- PureClean wash system with 5-stage filtration
- SmartDispense™ technology*
- DeepClean Cycle with Steam Prewash
- Eclipse black nylon deep-tiered four position adjustable upper rack
- Nylon utility shelves with StemSafe in upper rack
- 5 cycles/5 options
- Fan-assist dry



PDW7880P

GE Profile built-in dishwasher with front controls

- Four-position adjustable upper rack
- 4 utility shelves with StemSafe
- 2 sets of fold-down tines in lower rack
- CleanSensor™
- Up to 16-place setting capacity nylon racking
- Countdown display with 1-9-hour Delay Start
- Glasses selection



GDWT300R

GE stainless interior dishwasher with hidden controls

- PureClean wash system with 5-stage filtration
- SmartDispense™ technology*
- Steam Prewash
- Platinum silver nylon racks
- 3 cycles/5 options
- SaniWash cycle (NSF residential)
- Fan-assist dry



* Only GE has it!



WPDH8900J

GE Profile 4.2 IEC** cu. ft. colossal capacity frontload washer with Steam and SmartDispense technology***

- SteamRefresh
- Steam Assist
- SmartDispense technology***
- H2ition wash system
- Specialty cycles—Performance fabrics, Fleece, Pet bedding
- Stain Inspector™ stain removal system
- CleanSpeak™ washer/dryer communication
- 1300-RPM spin speed
- Wide base suspension



DPVH890EJ/GJ

GE Profile 7.5 cu. ft. colossal capacity frontload dryer with Steam technology

- SteamRefresh
- Steam Dewrinkle
- Fastest, most even dryer†
- Reverse tumble
- DuoDry™ heat management system
- Specialty cycles—Performance fabrics, Fleece, Pet bedding
- Baffle dry rack and hook system
- CleanSpeak™ washer/dryer communication
- Stainless steel dryer interior



SPBD880J

GE Profile SmartDispense frontload washer pedestal

- Automatically dispenses detergent and fabric softener
- Includes Stain Inspector
- Holds up to 6-month supply of detergent††
- Holds 95 ounces of fabric softener



SPSD157J

GE Profile 15" frontload storage pedestal

- Flexible multi-use storage
- Accommodates large additive bottles

GE clothes care



WBVH5300K

GE 4.0 IEC** cu. ft. king-size capacity frontload washer

- HydroMotion wash action
- PerfectTemp™
- Load-sensing adaptive fill
- 14 cycles
- 4 wash/rinse temperatures
- 1000-RPM spin speed
- QuietBalance™ suspension system



Shown with optional pedestal
SBSD137HWW



DBVH520EJ/GJ

GE 7.0 cu. ft. super capacity frontload dryer

- Sensor Dry Plus
- Dewrinkle cycle
- 4 custom heat settings
- Reversible 15" door with TrueGrip™ handle



Shown with optional pedestal
SBSD137HWW

*ADA compliant based on Uniform Federal Accessibility Standards
 **Washes equivalent amount of clothes as a similar cu. ft. agitator machine per IEC 60456 Edition 4.
 ***SmartDispense technology is not available without a SmartDispense pedestal which must be purchased separately.
 †Among premium frontload matching dryers, fastest drying performance is based on an 8-lb. AHAM load and 100% initial moisture content.
 ††Based on an 8-lb. AHAM load, 10 loads per week.
 ‡Most even drying performance is based on a percentage of remaining moisture content.

GE® clothes care



WCVH4800K/WCVH4815K

GE 2.6 IEC** cu. ft. extra-large capacity 24" frontload washer

- HydroMotion wash action
- HydroHeater™ internal water heater
- 1400-RPM spin speed
- 5 wash/spin speed combinations
- Multiple wash cycles
- 5 with Sanitize wash/rinse temperatures
- Delay start up to 18 hours



DCVH480EK/DCVH485EK

GE 4.0 cu. ft. large capacity 24" frontload dryer

- 5 heat selections
- Sensor Dry™
- Stainless steel drum
- Multiple dry cycles
- Cycle countdown display with LED indicators
- Delay start up to 18 hours



SBSD137H

Frontload pedestals

These optional 13" pedestals (sold separately) raise the door opening and the height of the washer or dryer. Feet on 13" pedestal allow it to adjust to 13-3/8" height.

GE Profile Harmony™ clothes care



WPGT9360E

GE Profile Harmony 4.0 IEC** cu. ft. king-size capacity washer

- HydroWash™ system with Infusor™
- HydroHeater internal water heater
- HydroView™ glass lid
- English/Spanish LCD option
- Direct-drive motor with adaptive spin-speed combinations
- Flow-Thru™ dispensing system
- Stain Inspector™ system
- Stainless steel basket
- Adaptive water levels



DPGT750EC/GC

GE Profile Harmony 7.3 cu. ft. king-size capacity dryer

- Specialty cycles
- CleanSpeak™ washer/dryer communication
- English/Spanish LCD option
- Full electronic controls with touchscreen
- DuoDry™ system
- Delicate Cycle with extra-low heat setting
- Stainless steel drum
- 5 heat selections
- Adaptive cool-down
- Wrinkle care extended tumble



GE Café™ counter-depth side-by-side refrigerator

	GE Café
	CSCP5UGX
Counter-depth	●
Capacity	
Total (cu. ft.)	24.6
Fresh food (cu. ft.)	15.3
Freezer (cu. ft.)	9.3
Shelf area (sq. ft.)	20.7
Fresh food features	
ClimateKeeper™ system	ClimateKeeper2™
Multi-flow air system	●
Electronic sensors	●
Actual-temperature display	●
External controls	●
TurboCool™ setting	●
GE water filtration system	MSWF
UltraFlow ¹⁰⁰ dispenser	Crushed ice, cubes, water
Light	●
Child lock and door alarm	●
Quick Ice™ feature	●
Water filter indicator light	●
Cabinet shelves	3 glass
Adjustable	3
Slide-out, spillproof	2
QuickSpace™ shelf	●
Integrated shelf support system	●
Snugger™ clips	2
Freshness Center™ (3-stack drawer system)	●
Top drawer	Adj. temp.
Middle drawer	Adj. humidity
Bottom drawer	ExpressChill™
ClearLook™ door bins	5 (4 adj.; 2 w/gallon storage)
In-the-door beverage storage	Wire beverage rack
BrightSpace™ interior lighting	GE Reveal®
Quiet design	Premium
Freezer features	
FrostGuard™ technology	●
Integrated Ice™ system	●
Wire slide-out baskets	3 (2 full-extension)
Wire cabinet shelves	3
Wire tilt-out door bins	2 adj.
Door bin	1
BrightSpace interior lighting	GE Reveal
Exterior	
Color(s) available*	SS
Door handles	GE Café stainless
Exterior design	Stainless
Textured steel case	Top only
Stainless steel side panels	●
Adjustable rollers	Front
Weights & Dimensions	
Height to top of hinge (in.)	72-1/8
Height to top of case (in.)	71-5/8
Case depth without door (in.)†	23-7/8
Case depth less door handle (in.)†	27-1/8
Case depth with door handle (in.)†	29-3/4
Depth w/fresh food door open 90° (in.) †	46
Width (in.)	36
Width w/door open 90° w/door handle (in.)	41-5/8
Air clearances	Each side (in.) 1/8 Top (in.) 1 Back (in.) 1/2
Approximate shipping wt. (lbs.)	424
Power/Rating	120V, 60Hz, 15Amps

*Color(s) available: SS = Stainless steel
†Water hook-up fits in back air clearance when calculating installation depth.

If installed against a wall, allow clearance of 14-1/4" on 25 cu. ft. on freezer side to remove ice bin. To remove fresh food pans, remove door bins. Clearances required to remove fresh food full-size pan without disassembling: 19" on 25 cu. ft. Allow additional space for any necessary leveling adjustments.

ALL MODELS AVAILABLE IN U.S. AND CANADA.

GE side-by-side refrigerators

	GE "W" Series
	GSS25WST GSS25WGT
ADA compliant	●
Capacity	
Total (cu. ft.)	25.4
Fresh food (cu. ft.)	15.91
Freezer (cu. ft.)	9.48
Shelf area (sq. ft.)	22.9
Fresh food features	
Actual-temperature display	●
GE water filtration system	MWF
UltraFlow dispenser	64 Crushed ice, cubes, water
Features	
Light and child lock	●
Door alarm	●
Water filter indicator light	●
Cabinet shelves	3 glass
Adjustable	3
Slide-out, spillproof	3
Integrated shelf support system	●
Snugger clips	2
Freshness Center	●
2-stack drawer system	●
Top drawer	1 adj. temp.
Bottom drawer	1 adj. humidity
Snack drawer	●
Door bins	4 (2 adj. with gallon storage)
Dairy compartment	●
Interior lighting	Dual
Quiet design	Deluxe
Freezer features	
FrostGuard technology	●
Factory-installed icemaker and bin	●
Wire cabinet shelves	4 (3 adj.)
Storage basket(s)	1 slide-out
Door bins	5 shelves
Interior light	●
Appearance	
Color(s) available*	SS WW, CC, BB Stainless steel tubular CM
Door handles*	Rounded doors
Exterior design	Black & bottom bevels
Textured steel case	●
Stain, steel side panel accessory (opt.)	●
Adjustable rollers	Front
Weights & Dimensions	
Height to top of hinge (in.)	69-1/2
Height to top of case (in.)	68-3/4
Case depth without door (in.)†	28
Case depth less door handle (in.)†	31-1/4
Case depth with door handle (in.)†	33-5/8
Depth w/fresh food door open 90° (in.)†	50-1/8
Width (in.)	35-3/4
Width w/door open 90° with door handle (in.)	40-3/4
Air clearances	Each side (in.) 1/8 Top (in.) 1 Back (in.) 1
Approx. shipping wt. (lbs.)	344
Power/Ratings	120V, 60Hz, 15Amps

*Color(s) available: SS = Stainless steel, WW = White, CC = Bisque, BB = Black, CM = Color-Matched.

†Water hookups fits in back air clearance when calculating installation depth. If installed against a wall, allow clearance of 14-1/4" on 25 cu. ft. models on freezer side to remove bin. Clearances required to remove fresh food full-size pan without disassembling: and 19" on 25 cu. ft. Allow additional space for any necessary leveling adjustments.

ALL MODELS AVAILABLE IN U.S. AND CANADA.

GE Profile™ bottom-freezer refrigerator

	GE Profile
	PFSS2MIY PFSS2MIY
ENERGY STAR® qualified	●
Stainless steel model	● / -
French-door model	●
Capacity	
Total (cu. ft.)	22.2
Fresh food (cu. ft.)	15.5
Freezer (cu. ft.)	6.7
Shelf area (sq. ft.)	27.7
Fresh food features	
ClimateKeeper system	●
Door alarm	●
Internal electronic temperature controls	●
TurboCool setting	●
Cabinet shelves	4 glass
Adjustable	4 split
Slide-out	2
Spillproof	3
QuickSpace shelf	●
Internal water dispenser	●
GE water filtration	MWF
Water filter indicator light	●
Freshness Center	●
Crisper drawers	2 adj. humidity
Snack drawer	1 adj. temp
ClearLook adjustable gallon door bins	3
Fixed door bins	2
In-the-door beverage storage	ShelfSaver beverage rack
Snugger™ clips	2
Dairy compartment	●
BrightSpace™ interior lighting	GE Reveal
Quiet design	Premium
Freezer features	
Factory-installed icemaker & bin	●
FrostGuard technology	●
Multi-level Slide 'n Store™ full-extension freezer baskets	2 f/w, 1 split
BrightSpace interior lighting	GE Reveal
Exterior	
Color(s) available*	SS WW, BB Stainless steel Color-matched
Sculptured door handles	Contoured w/top & bottom bevels
Exterior design	Gray Color-matched
Textured steel case	Stainless High-gloss
Door	●
Door stops	●
Adjustable rollers	Front
Weights & Dimensions	
Height to top of hinge (in.)	68-1/2
Height to top of case (in.)	67-3/4
Case depth without door (in.)†	28-3/4
Case depth less door handle (in.)†	33
Case depth with door handle (in.)†	35-1/2
Depth w/fresh food door open 90° (in.)†	46-5/8
Width (in.)	32-3/4
Width w/door open 90° w/door handle (in.)	40-5/8
Air clearances	Each side (in.) 1/8 Top (in.) 1 Back (in.) 3/4
Approximate shipping wt. (lbs.)	315
Power/Rating	120V, 60Hz, 15Amps

*Color(s) available: SS = Stainless steel, WW = White, BB = Black.
†Water hook-up fits in back air clearance when calculating installation depth.

ALL MODELS AVAILABLE IN U.S. AND CANADA.



Listed by Underwriters Laboratories

GE® top-freezer refrigerator

	GE "K" Series
	GTH21KCX GTL21KCX GTH21SCX
ENERGY STAR® qualified	●
Capacity	
Total (cu. ft.)	21.0
Fresh food (cu. ft.)	14.9
Freezer (cu. ft.)	6.1
Shelf area (sq. ft.)	24.5
Fresh food features	
Upfront temperature controls	●
Cabinet shelves	4 glass
Adjustable	4 split
Spillproof	4 (resistant)
Crisper drawers	2 adj. humidity
Snack drawer	●
Fixed door bins	3 (2 with gallon)
Dairy compartment	●
Interior lighting	●
Quiet Design	Deluxe
NeverClean condenser	●
Freezer features	
Factory-installed icemaker and bin	●
Wire freezer compartment shelves	1 f/w wire (2 pos.)
Fixed door bins	2 full-width
Exterior	
Color(s) available*	WW, CC, BB CleanSteel™ SS CM Black
Door handle(s)*	Case only (black)
Customer-installed handles	●
Exterior design	Rounded doors
Textured steel door and case	●
Reversible doors	●
Adjustable rollers	Front
Weights & Dimensions	
Height to top of hinge (in.)	66-3/4
Height to top of case (in.)	66
Height to mid-freezer (in.)	55
Case depth without door (in.)	27
Case depth less door handle (in.)	30-1/2
Case depth with door handle (in.)	31-3/4
Depth w/fresh food door open 90° (in.)	60-3/4
Width (in.)	32-3/4
Width w/door open 90° w/door handle (in.)	36-1/2
Air clearances	Each side (in.) 1/8 Top (in.) 1/2 Back (in.) 1/2
Approx. shipping wt. (lbs.)	219
Power/Ratings	120V, 60Hz, 15Amps

*Color(s) available: SS = Stainless steel, CleanSteel = Stainless appearance, WW = White, CC = Bisque, BB = Black, CM = Color-Matched.
ALL MODELS AVAILABLE IN U.S. AND CANADA.

30" built-in double oven

	GE Profile™
	Convection double oven
	PT956SM PT956WM PT956CM PT956BM
Features	
Capacity (cu. ft.) (upper/lower)	4.4/4.4
Oven	Upper Convection/self-clean Lower Thermal/self-clean
Cleaning time	Variable
Automatic self-clean oven door lock	●
Self-clean oven w/Delay Clean option	●
Light self-clean option	●
TrueTemp™ oven system	●
Hidden bake oven interior	●
Variable broil/Six-pass broil element	●
Eight-pass bake element	●
PreciseAir™ convection system	Upper
Convection bake	Multi/single-rack
Convection roast	Upper
Auto Recipe™ conversion	Upper
QuickSet controls	Glass touch
Proof mode	Upper
Oven meat probe	Upper
Warm mode	Upper
Temperature display	●
Delay bake option	●
C° and F° programmable	●
Audible preheat signal	●
Auto oven shut-off w/override	●
Electronic clock and kitchen timer	●
Control lock capability	●
Oven light	2
Certified Sabbath mode	●
Flat convection cover	●
QuietBake™ fan system	●
Oven racks	Upper 3 heavy-duty Lower 2 heavy-duty
Self-clean oven racks	●
Embossed rack positions	7 upper/7 lower
Appearance	
Color appearance*	SS WW CC BB
Frameless oven doors	Stainless steel White glass Bisque glass Black glass
Big ClearView™ windows	● Sculptured Stainless steel Sculptured white Sculptured bisque Sculptured black
Oven door handles	
Weights & Dimensions	
Approx. shipping wt. (lbs.)	256
Oven cabinet width required (in.)	30
Overall oven interior dimensions (WxHxD in inches)	29-3/4 x 52-7/8 x 23-1/2
(Overall oven interior dimensions (WxHxD in inches) (Upper)	24 x 17-1/2 x 18-1/4
Overall oven interior dimensions (WxHxD in inches) (Lower)	24 x 17-1/2 x 18-1/4
Power/Ratings	
KW rating @ 240V	9.0
208V	6.8
Amps @ 240V	40
208V	40
Convection wattage	2500
Broiler/bake wattage	2400/2100

*SS = Stainless steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.

30" built-in single ovens

	GE Profile	GE
	Single-double oven	Convection single oven
	PT925SN PT925DN	PT916SM PT916WM PT916CM PT916BM
		Single oven
		JTP30SP JTP30DP
ADA-compliant	●	●
Features		
Oven capacity (cu. ft.)	5.0	4.4
Oven	Convection/self-clean	Convection/self-clean
Cleaning time	Variable	Variable
Automatic self-clean oven door lock	●	●
Self-clean oven with Delay Clean option	●	●
Light self-clean option	●	●
TrueTemp oven system	●	●
Hidden bake oven interior	●	●
Variable broil/Six-pass broil element	●	●
Eight-pass bake element	●	●
PreciseAir convection system	Lower oven	●
Convection bake	Lower oven	Multi-/single-rack
Convection roast	Lower oven	●
Auto Recipe conversion	●	●
QuickSet controls	Glass touch	Glass touch
Proof mode	●	●
Warm mode	●	●
Oven meat probe	Lower oven	●
Temperature display	●	●
Delay bake option	●	●
C° and F° programmable	●	●
Audible preheat signal	●	●
Auto oven shut-off w/override	●	●
Electronic clock and kitchen timer	●	●
Control lock capability	●	●
Oven light	●	2
Certified Sabbath mode	Lower oven	●
Flat convection cover	Lower oven	●
QuietBake fan system	●	●
Oven racks	3 heavy-duty	3 heavy-duty
Self-clean oven racks	●	●
Embossed rack positions	2 upper	7
Appearance		
Color appearance*	SS WW CC BB	SS WW CC BB
Frameless oven door	Stainless steel Black glass	Stainless steel White glass Bisque glass Black glass
Big ClearView window	● Sculptured stainless steel Sculptured black	● Sculptured stainless steel Sculptured white Sculptured bisque Sculptured black
Oven door handle	●	●
Undercounter installation	●	●
Weights & Dimensions		
Approx. shipping wt. (lbs.)	212	140
Oven cabinet width required (in.)	30	30
Overall dimensions (WxHxD in inches)	29-3/4 x 28-1/4 x 23-1/2	29-3/4 x 28-1/4 x 23-1/2
Overall oven interior dimensions (upper) (WxHxD in inches)	24 x 8-3/4 x 17-7/8	24 x 17-1/2 x 18-1/4
Overall oven interior dimensions (lower) (WxHxD in inches)	24 x 12-1/2 x 16	24 x 17-1/2 x 18-1/4
Power/Ratings		
KW rating @ 240V	3.9	4.5
208V	2.9	3.4
Amps @ 240V	20	20
208V	20	20
Convection wattage	1300	2500
Broiler/bake wattage	2750/1700 (upper) 2950/2200 (lower)	2400/2100

*SS = Stainless steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.



30" GE Profile free-standing CleanDesign™ electric range

	GE Profile
	PB975SP PB975TP PB975DP
Features	
Self-clean oven	●
Self-clean latch	Auto
Oven capacity (cu. ft.) (upper/lower)	2.2/4.4
Hidden bake oven interior	Lower
Self-clean oven racks	4 heavy-duty, self-clean
	Black True white Black
Ceramic-glass cooktop	
One-piece upswept cooktop	●
12"/9"/6" tri-ring element	1 (3000W)
7" ribbon heating element	2 (1800W)
Bridge element	1 (800W)
6" element	1 (1500W)
6" warming zone	1 (120W)
Melt/Simmer	● / ●
Infinite heat controls	●
TrueTemp oven system	●
Six-pass power bake element	8 pass
Six-pass broil element	8 pass
PreciseAir	●
Convection cook	●
QuickSet oven controls	QuickSet VI
Warm mode	●
Pizza mode	●
Slow cook mode	●
Digital temperature display	Digitemp
Oven function icons	●
Delay bake	●
Oven light pad	●
Control lock capability	●
Self-clean cool-down time display	●
Light self-clean option	●
Delay clean option	●
Auto oven shut-off	●
Certified Sabbath mode	●
Audible preheat signal	●
Dual element bake	●
Oven meat probe	●
Hot surface lights	5
Oven "ON" light	●
Self-clean cycle light	Display
Interior oven light	●
Upper oven	●
Appearance	
Color appearance*	SS/WW/BB
	Stainless steel White Black
Frameless glass oven door	
Oven door with window	Big ClearView
Heavy-duty knobs	SS model
Designer-style handle	Sculptured
Weights & Dimensions	
Overall oven interior dimensions (WxHxD in inches) upper/lower	24 x 8-7/8 x 18 24 x 17-1/2 x 18-1/4
Approx. shipping wt. (lbs.)	247
Power/Ratings	
KW rating @ 240V	14.3
208V	10.7
Amp rating @ 240V / 208V	40
Convection wattage	2500
Broiler/bake wattage	3600/2650

*SS = Stainless steel with black accents, BS = CleanSteel with black accents, WW = White with white glass door, BB = Black with black glass door.


All ranges are shipped with cooktop cleaning creme & pad.

30" GE free-standing CleanDesign electric range

	GE
	JBP66SM JBP66DM JBP66MN
Features	
Self-clean oven	●
Self-clean latch	●
Oven capacity (cu. ft.)	5.3
Oven racks	2
	Pat. black Pat. white Pat. bisque Black Pat. black
Ceramic-glass cooktop	
One-piece upswept cooktop	●
9"/12" dual element	1 (3000W)
8" ribbon heating element	1 (2000W)
6" ribbon heating element	2 (1500W)
6" warming zone	1 (120W)
Melt/Simmer	●
Infinite heat controls	●
TrueTemp oven system	●
Six-pass power bake element	●
QuickSet oven controls	QuickSet IV
Digital temperature display	●
Delay bake	●
Oven light pad	●
Self-clean cool-down time display	●
Delay clean option	●
Auto oven shut-off	w/override
Certified Sabbath mode	●
Audible preheat signal	●
Dual element bake	●
Hot surface lights	●
Interior oven light	Pad
Storage drawer	●
Appearance	
Color appearance*	SS/BS/WW/CC/BB
	Stainless steel CleanSteel White Bisque Black
Frameless glass oven door	
Oven door with window	Big hearth
Designer-style handle	●
	Stainless Recessed Recessed Recessed
Storage drawer handle	Recessed
Weights & Dimensions	
Overall oven interior dimensions (WxHxD in inches)	24-1/8 x 19-1/2 x 19-3/8
Approx. shipping wt. (lbs.)	175
Power/Ratings	
KW rating @ 240V	11.9
208V	8.9
Amp rating @ 240V / 208V	40
Broiler/bake wattage	3410/2585

*SS = Stainless steel with black accents, BS = CleanSteel with black accents, WW = White with white glass door, CC = Bisque with bisque glass door, BB = Black with black glass door.

All ranges are shipped with cooktop cleaning creme & pad.



Backguard is 30-7/8" wide on model JBP66.*

GE Café™ 30" free-standing gas range

	GE Café
	CGS980SEM
Features	
Upper oven capacity	Super-large 5.0 cu. ft.
Lower oven capacity	1.0 cu. ft.
Self-clean oven with Delay Clean option	●
Light self-clean option	●
Variable cleaning time	●
Automatic self-clean oven door lock	●
Oven racks	3 heavy-duty self-clean
TrueTemp oven system	●
Cooktop	Stainless Steel
Deep-recessed cooktop	●
PowerBoil™ burner	(1) 17,000 BTU
Dual-flame stacked burner	(1) 18,000 BTU/ 140° simmer
Precise Simmer burner	(1) 5,000 BTU/ 140° simmer
All-purpose burners	(1) 9,100 BTU
Center oval burner	6,000 BTU
Non-stick griddle	Included
Continuous grates	Self-clean
Ignition system	Electronic
PreciseAir convection system	●
Convection bake	Single-/multi-rack
Convection roast	●
Auto Recipe conversion	●
Electronic controls	QuickSet VI Glass touch
Oven meat probe	●
Closed door broiling	●
Temperature display	●
Delay Bake option	●
C° or F° programmable	●
Audible preheat signal	●
Auto oven shut-off w/override	●
Gas cooktop and oven lock-out	●
Electronic clock/kitchen timer	●
Certified Sabbath mode	●
Interior oven light	●
Lower oven (140° to 450°)	●
Appearance	
Color appearance*	SS
Frameless oven door	Stainless steel
Oven door with window	Big ClearView
Sculptured oven door handle	●
Heavy-duty knobs	●
Dishwasher-safe knobs	●
Lower oven/Storage drawer handle	Commercial
Weights & Dimensions	
Overall oven interior dimensions (WxHxD in inches)	24 x 19 x 19
Approx. shipping wt. (lbs.)	245
Power/Ratings	
	(1) 17.0/11.0 (1) 18.0/15.0 (1) 5.0/4.0 (1) 9.1/8.0 (1) 6.0/6.0
Top burners (000's BTUs) Nat/LP	
Range electrical rating	120v, 60Hz, 15A
Convection wattage	1,200
Broiler/Bake BTU	13,500/16,000 BTU
LP conversion kit (included)	●

*SS = Stainless steel Factory set for Natural Gas. A set of LP orifices is included with each range for LP conversion.

Optional kit for 30" GE Café gas range (Available at additional cost)

Accessory backguard (Attaches to the back of range as a backguard when unit is installed in 30" free-standing cutout) JXS80SS—Stainless steel

30" self-clean gas range

GE Profile™	
Sealed burner	
PGB908SEM PGB908DEM	
Capacity	
Upper oven capacity	Super-large 5.0 cu. ft.
Features	
Oven cleaning	Self-clean
Deep-recessed cooktop	●
Cooktop burners	Sealed
PowerBoil™ burner (Nat.)	(1) 17,000 BTU
Precise Simmer burner (Nat.)	(1) 5,000 BTU/140° Simmer
High-output burner (Nat.)	(1) 11,000 BTU
All-purpose burners (Nat.)	(1) 9,100 BTU
Center oval burner	(1) 6,000 BTU
Non-stick griddle	Included
Valves (degree of turn)	270
TrueTemp™ oven system	●
QuickSet oven controls	QuickSet V
Oven control setting	DigiPad
Auto self-clean	●
Electronic oven control	●
Delay Bake	●
Hi/Low broil	●
Electronic clock and timer	●
Automatic oven timer	●
Audible preheat signal	●
Auto oven shut-off	●
Certified Sabbath mode	●
Oven lock-out capability	●
One-piece upswept cooktop	Porc.-enam. Matte black heavy-cast Grey heavy-cast Taupe heavy-cast Black heavy-cast
Removable grates	●
Continuous grates	Dishwasher-safe
Ignition system	Electronic
Warming drawer (140° to 220°)	●
Oven racks	2
Six embossed rack positions	●
Scratch-resistant backguard	Stainless steel Porc.-enam.
Interior oven light	●
In-oven broiling	●
Appearance	
Color appearance*	SS/WW/CC/BB Stainless steel White glass Bisque glass Black glass
Frameless oven door	●
Oven door with window	Big ClearView™
Stainless appearance knobs	SS model
Oven door handle	Sculptured
Weights & Dimensions	
Overall oven interior dimensions (WxHxD in inches)	24 x 19 x 19
Approx. shipping wt. (lbs.)	235
Power/Ratings	
	(1) 17.0/11.0 (1) 6.0/6.0 (1) 11.0/9.1 (1) 5.0/4.0 (1) 9.1/8.0
Top burners (000's BTUs) Nat/LP	
Oven/broiler burners (000's BTUs) Nat/LP	16.0/16.0 oven 13.5/12.0 broil
Gas range electrical rating**	120V, 60Hz, 9A
LP conversion kit (includ.)	●

*SS = Stainless steel (with black/metallic accents on select models), BC = Soft stainless with black accents, WW = White with white glass door, CC = Bisque with bisque glass door, BB = Black with black glass door.

**15A requires a dedicated circuit. Factory set for Natural Gas. A set of LP orifices is included with each range for LP conversion.

Built-in CleanDesign™ cooktops

GE Profile		
	PP975SM PP975BM	PP950SM PP950BM
ADA-compliant	●	●
Features		
Ceramic-glass surface	Black Black	Black Black
Number of elements	5 ribbon	4 ribbon
12"/9"/6" tri-ring element	1 ribbon (3000W)	
6"/9" dual heating element		1 ribbon (2500W)
5"/8" dual heating element	1 ribbon (2200W)/ 1 PowerBoil (2400W)	1 ribbon (2200W)
7" heating elements		1 ribbon (1500W)
6" heating elements	1 ribbon (1200W)	1 ribbon (1200W) w/warmer
6" warming zone	1 ribbon (120W)	
Hot surface indicator lights	5	4
Precise Digital Control System™		●
Pan presence sensor		●
Pan size sensor		●
Kitchen timer		●
Control lock capability	●	●
Appearance		
Color appearance*	SS BB	SS BB
Frameless	BB	BB
Stainless steel frame	SS models only	SS models only
Weight & Dimensions		
Cooktop width (in inches)	36	30
Approx. shipping wt. (lbs.)	44	38
Power/Ratings		
KW rating @ 240V	8.9	7.4
208V	6.7	5.6
Amps @ 240V	40	40
208V	40	30

*SS = Stainless Steel, BB = Black on black.

Built-in gas cooktops

GE Profile		
	JGP970SEK JGP970TEK JGP970KEK JGP970BEK	JGP940SEK JGP940TEK JGP940KEK JGP940BEK
ADA-compliant	●	●
Features		
Cooktop burners	5 sealed	4 sealed
PowerBoil burner (000's BTUs)	(1) 15.0 180° simmer	(1) 15.0 180° simmer
All-purpose burner(s) (000's BTUs)	(1) 11.0 (1) 9.1 150° simmer	(1) 11.0 (1) 9.1 150° simmer
Precise Simmer burner(s) (000's BTUs)	(2) 6.0 140° simmer	(1) 6.0 140° simmer
Electronic pilotless ignition	●	●
Cooktop surface	Ceramic-glass	Ceramic-glass
Cooktop grates	Matte black deluxe-cast Grey deluxe-cast Taupe deluxe-cast Black deluxe-cast	Matte black deluxe-cast Grey deluxe-cast Taupe deluxe-cast Black deluxe-cast
Continuous grates	●	●
Dishwasher-safe grates and knobs	●	●
Control panel	Black True white Bisque Black	Black True white Bisque Black
Controls	Upfront	Right side
Control lock capability	●	●
Appearance		
Color appearance*	SS WW CC BB	SS WW CC BB
Heavy-duty knobs	SS models only	SS models only
Weights & Dimensions		
Cooktop width (in inches)	36	30
Approx. shipping wt. (lbs.)	59	52
Features		
Gas cooktop electrical rating	120V, 60Hz, 5A	
Burners (000's/BTU's): Natural Gas/LP Gas †	(1) 15.0/13.0 (1) 11.0/9.1 (1) 9.1/8.1 (2) 6.0/6.0	(1) 15.0/13.0 (1) 11.0/9.1 (1) 9.1/9.1 (1) 6.0/6.0

*SS = Stainless Steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.

†A set of LP orifices is included with each cooktop for LP conversion. Factory set for natural gas.

36" designer hood

GE Profile wall mount		
JV966D		
General		Appearance
Width	36"	Color appearance*
Height	18"	SS
Features		Weights & Dimensions
Ducting	Vertical only	Approx. shipping wt. (lbs.)
Duct size	7" round	77
CFM rating	600	Power/Ratings
Sones rating	7	Current rating amps @ 120V
Filters	●	3.9
Filter cleaning	Dishwasher-safe	Accessories/Kits
Lighting	Dual halogen	Baffle filter kit
Control type	Manual	Available
Control location	Hidden	Optional chimney kit
Four-speed fan control	●	Available
Light settings	Off/High/Night	
Blower/light switch color	Black	

*SS= Stainless steel.

36" Hoods

36" Width	GE Profile	
	High-performance	
	JV666H	JV665H
Features		
Four-speed fan control	●	●
Damper included (rectangular)	●	●
Optional damper accessory (round)	JXDA22	JXDA22
CFM/Sones rating:		
Back rectangular	390/7.5	390/7.5
Top round	410/7.0	410/7.0
Top rectangular	380/7.5	380/7.5
Removable grease filters	2 ¹	2 ¹
	2 halogen (50-watt)	2 halogen (50-watt)
Cooktop light(s)*		
Night light position on light switch	●	●
3-1/4" x 10" rectangular duct	●	●
7" round duct	●	●
Appearance		
Color appearance**	SS	WW/BB
Weights & Dimensions		
Approx. shipping wt. (lbs.)	35	35
Power/Ratings		
Current rating amps @ 120V	2.5	2.5

*Light bulbs not furnished.
**SS = Stainless steel, WW = White on white, BB = Black on black.
†WB02X11011 (30") or WB02X11012 (36") removable grease filter is available for additional cost.
Call toll-free 800.626.2002.

30" Hoods

30" Width	GE Profile	
	Performance	
	JV536H	JV535H
Features		
Two-speed fan control	●	●
Damper included (rectangular)	●	●
Optional damper accessory (round)	JXDA22	JXDA22
CFM/Sones rating:		
Back rectangular	240/4.5	240/4.5
Top round	250/4.5	250/4.5
Top rectangular	240/5.0	240/5.0
Removable grease filters	2 ¹	2 ¹
	2 halogen (50-watt)	2 halogen (50-watt)
Cooktop light(s)*		
Night light position on light switch	●	●
3-1/4" x 10" rectangular duct	●	●
7" round duct	●	●
Non-vented	Optional	Optional
Appearance		
Color appearance**	SS	WW/CC/BB
Weights & Dimensions		
Approx. shipping wt. (lbs.)	30	30
Power/Ratings		
Current rating amps @ 120V	1.4	1.4

*Light bulbs not furnished. Light cover not included on JV338H and JN327H.
**SS = Stainless steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.
†WB02X10707 (30") or WB02X10708 (36") removable charcoal filter is available for additional cost.
Call toll-free 800.626.2002.

GE Profile Advantium® wall oven

	GE Profile	
	PSB2201NSS PSB2200NWW PSB2200NBB	
Features		
Family-size oven		1.7
Stainless steel oven interior		●
Cooking modes	Speedcook	up to 8 times
	Convection oven	250°-450°
	Microwave oven	●
	Warming	●
	Proof	●
	Multilevel	True European Convection
Oven controls	Controls	Dial & glass touch
	Electronic scrolling display	●
	Preprogrammed menu items	175
	Help pad	●
	Demo mode	●
	Interior oven light	●
	Beeper sound level control	4 levels
	Variable scroll speed	5 speeds
Heating elements	Upper heater power (watts)	2400
	Lower heater power (watts)	500
	Convection heater power (watts)	1500
Custom recipe saver		30
Cooking complete reminder		●
Control lockout		●
Frameless glass oven door with window		●
Microwave oven features	Sensor	●
	Defrost—Auto/Time/1-lb. Quick	●
	Soften/Melt	●
	Microwave power output watts	950
27"/30" appearance		30"
Appearance		
Color appearance		Stainless steel White Black
Profile sculptured handle		●
Weights & Dimensions		
Overall oven interior dimensions (in inches)	Height	8-1/2
	Width	20-1/16
	Depth	17
Overall dimensions (in inches)	Exterior width (W)	29-25/32
	Exterior height (H)	19-1/32
	Exterior depth, not including handle (D)	21-1/2
Oven cabinet width required (in inches)		30
Cutout height		17-1/2
Cutout width		25-1/8
Cutout depth		23-1/2
Approx. shipping weight (lbs.)		115
Power/Ratings		
Input volt/hertz		240V/208V 60Hz
Input amps/watts (max)		30A/6.3KW-total
Accessories		
Cookbook		●
Cooking guide		●
Grill tray		●
Cooking tray		●
Microwave tray		●
Rack		Full-width JX2201NSS N/A JX2200NBB
Storage drawer		
Warranty		
Limited one-year in-home warranty*		●
Limited five-year magnetron warranty*		●

GE Profile		SCA1001KSS SCA1000HWW SCA1000HBB
Features		
Family-size oven		●
Stainless steel oven interior		●
Cooking modes	Speedcook	up to 4 times
	Traditional oven	●
	Microwave oven	●
	Warming	●
Oven controls	Controls	Dial & buttons
	Electronic scrolling display	●
	Preprogrammed menu items	over 100
	Help pad	●
	Demo mode	●
	Interior oven light	●
	Beeper sound level control	4 levels
	Variable scroll speed	5 speeds
	Custom Recipe Saver	30
Cooking complete reminder		●
Control lockout		●
High-capacity cooktop vent fan		2 speeds
Full-view cooktop lighting		●
Programmable night light		●
Microwave oven features	Sensor	●
	Defrost	●
	Microwave power output watts	900
	300-CFM vent fan	●
Appearance		Stainless steel White Black
Color appearance		
New Profile sculptured handle		●
Weights & Dimensions		
Overall oven interior dimensions (in inches)	Height	8-7/32
	Width	21-3/32
	Depth	14-3/32
Overall dimensions (in inches)	Exterior height (front)	16
	Exterior height (rear)	16-13/32
	Exterior width	29-7/8
	Exterior depth (not including handle)	15-3/8
Approx. shipping weight (lbs.)		95
Power/Ratings		
Input volt/hertz		120V/60Hz
Input amps/watts (max)		15A/1.7KW-total
Accessories		
Cookbook		●
Cooking guide		●
Cooking tray		●
Microwave tray		●
Recirculating charcoal filter kit (opt.)		JX81A
Filler panel kit**		Optional
Warranty		
Limited one-year in-home warranty*		●
Limited five-year magnetron warranty*		●

GE Profile Advantium above-the-cooktop oven

*See written warranty for details.
**Available through GE Parts. Call 1-877-959-8688

240-volt electric wall ovens are not approved for installation with a plug and receptacle. They must be hard wired in accordance with installation instructions.

Important: Before installing, consult installation instructions packed with product for current dimensional data.

Note: Cabinets installed adjacent to wall ovens must have an adhesion spec of at least a 194°F temperature rating.



GE Café™ 2.0 microwave oven

		GE Café
		CVM2072SM
Capacity		
Oven cavity (cu. ft.)		2.0
Features		
Watts (IEC-705 test procedure)		1100
EasyGuide™ menu system		Blue
Sensor controls		●
Power levels		10
Dual distribution cooking system		●
Kitchen timer		●
315-CFM vent fan/Boost		4-speed / ●
Cavity lighting		Halogen
Cooktop lighting		Halogen
Recessed turntable		●
Turntable On/Off		●
Easy-mount installation		●
*COOK™ Touch-control features		Instant-on 30 sec. & 1-7 minutes
	Express Cook	
	Time Cook and Time Cook I & II	●
	Add 30 Seconds	●
	Select food	●
	Select beverage	●
	Soften	●
	Melt	●
	Delay Start	●
REHEAT Touch-control features	Select Food/Beverage	●
DEFROST Touch-control features	Select time	●
	Select weight	●
	Select food	●
	1-lb. Quick Defrost	●
	Soften	●
	Melt	●
	Delay	●
CUSTOM 1 and 2 Touch Controls		●
OPTIONS Touch-control features	Reminder (24 hr.)	●
	Beeper volume	●
	Filter reminder	●
	Clock w/Clock Saver	●
	Control lockout	●
	Cooking complete reminder	●
	Display On/Off	Auto sleep mode
	Help key	●
	Sleep mode/Wake-up touch	●
	Programmable night light	●
Interactive demo mode		●
Appearance		
Color appearance*		SS
Case color		Graphite grey with tactile vent/light buttons
LED, LCD display control panel		●
Sculptured handle		●
Weights & Dimensions		
Overall oven interior dimensions WxHxD (in inches)		21-9/16 x 10-9/16 x 14-13/16
Approx. shipping weight (lbs.)		72
Power/Ratings		
Input Volt/Hertz		120 V/60 Hz
Input Amps/Watts (max)		15A/1.58 KW
Accessories		
Oven rack(s)		2 (2 positions)
Recirculating charcoal filter kit†		JX81H (optional)
Filler panel kit††		JX52 (optional)
Warranty		
Limited one-year in-home warranty**		●
Limited five-year magnetron warranty**		●

*SS = Stainless steel, WW = White on white, BB = Black on black.

**See warranty for details.

†Optional for units that are not set as recirculating from the factory.

††JX52WH and JX52BL available through GE Parts starting 12/01/09. Call 1-877-959-8688 to order.

GE Profile Spacemaker® microwave ovens

		GE Profile™	
		JVM3670SK JVM3670WF JVM3670BF	PVM1870SM PNM1871SM* PVM1870DM
Capacity			
Oven cavity (cu. ft.)		1.8	1.8
Features			
Watts (IEC-705 test procedure)		1100	1100
Electronic touch controls		●	●
SmartControl system w/interactive display		●	●
Scrolling display		2-line	2-line
Clock and AM/PM pad		●	●
Variable scroll speed		●	●
Help pad		●	●
Bilingual display (English/Spanish)		●	●
Sensor controls	Beverage	●	●
	Chicken/Fish	●	●
	Popcorn	●	●
	Potatoes	●	●
	Reheat	●	●
	Vegetables	●	●
Custom pads		●	●
Express Cook (1-6 min.)		●	●
Instant On controls		●	●
Time cook	I & II		I & II
Add 30 Seconds		●	●
Auto/Time/1-lb. Quick Defrost		● / ● / ●	● / ● / ●
Melt		●	●
Power levels		10	10
Delay Start		●	●
CircuWave™ 1100 cooking system		●	●
Recessed turntable		●	●
Turntable On/Off		●	●
Halogen interior/cooktop lighting		●	●
Programmable night light		●	●
Timer On/Off		●	●
Cooking complete reminder		●	●
Control lockout		●	●
300-CFM exhaust fan/Boost		4-speed / ●	4-speed / ●
Appearance			
Color appearance**		SS WW BB	SS SS WW/CC/BB
Case color		Black White Black	Black Black White/Bisque/Black
Sculptured handle		●	●
Big view window		●	●
Weights & Dimensions			
36"-width application		●	●
Overall oven interior dimensions WxHxD (in inches)		21-29/32 x 9-1/2 x 14-19/32	21-29/32 x 9-1/2 x 14-19/32
Approx. shipping weight (lbs.)		80	68
Power/Ratings			
Input Volt/Hertz		120V/60Hz	120V/60Hz
Input Amps/Watts (max)		15A/1.58KW	15A/1.58KW
Accessories			
Cooking guide label		●	●
Oven rack(s)		1 (2 positions)	2 (2 positions)
Recirculating charcoal filter kit†		JX81B (optional)	JX81B (optional) JX81B (included) JX81B (optional)
Filler panel kit††		—	JX52 (optional)
Warranty			
Limited one-year in-home warranty†††		●	●
Limited five-year magnetron warranty†††		●	●

*Non-vented model.

**SS = Stainless steel, WW = White on white, CC = Bisque on bisque, BB = Black on black.

†Optional for units that are not set as recirculating from the factory.

††JX52WH and JX52BL available through GE Parts starting 12/01/09.

Call 1-877-959-8688 to order.

†††See warranty for details.

GE Profile microwave oven

		GE Profile
		Extra-large PEB2060SM PEB2060DM
ADA compliant		
●		
Capacity		
Oven cavity (cu. ft.)		2.0
Features		
Watts (IEC-705 test procedure)		1200
Electronic touch controls		●
Scrolling display with Help pad		●
Demo mode		●
Electronic digital display w/clock		●
Display On/Off		●
Sensor controls	Popcorn	●
	Beverage	●
	Reheat	●
	Vegetable	●
	Potato	●
	Chicken	●
Express Cook		1-6 min.
Instant On controls		●
Time Cook		I & II
Add 30 Seconds		●
Auto/Time Defrost		●
Power levels		10
Turntable		●
Kitchen timer/Timer on/off		— / ●
Delay Start/Reminder		●
Cooking complete reminder		●
Control lockout		●
Appearance		
Color appearance*		SS WW/CC/BB
Case color		Black White, Bisque, Black
Door color		SS* White, Bisque, Black
Weights & Dimensions		
Approx. shipping weight (lbs.)		48
WxHxD (in inches)		16-11/16 x 11-1/4 x 18-1/16
	Cavity	24 x 13-25/32 x 19-13/32
	Exterior**	
Power/Ratings		
Input Volt/Hz		120/60
Electric input	Watts	1650
@ 120V	Amperage	13.9
Accessories		
Cooking guide label		●
Optional built-in kit†		●
Right-angle plug		●
Warranty		
Limited one-year in-home warranty***		●
Limited five-year magnetron warranty***		●

*SS = Stainless steel, WW = White on white, CC = Bisque on bisque, BB = Black on black

**Exterior dimensions: height includes feet, depth does not include handle.

***See written warranty for details.

GE Café and GE Profile stainless interior dishwashers

	GE Café CDWT980RSS	GE Profile PDWT480RSS PDWT400RWW PDWT400RBB
2009 ENERGY STAR®	●	●
Energy Factor (EF)*	0.66	0.66
Maximum gallons per cycle**	5.6	5.6
Kilowatt hrs/yr	324	324
Features		
SmartDispense™ technology	47 fl. oz.	47 fl. oz.
Tube and door liner	Stainless steel	Stainless steel
Place settings	Up to 16	Up to 16
Front appearance	Café flat door	Contour door
Wash system	PureClean	PureClean
Wash arms	3 direct-feed	3 direct-feed
Wash levels	6-towerless	6-towerless
Water filtration	5-stage with ExtraFine™ filter	5-stage with ExtraFine filter
Dual pumps and motors	●	●
Hard-foed disposer	Piranha™	Piranha
Sensor	CleanSensor™	CleanSensor
Automatic temp. control	●	●
Rinse aid dispenser	w/indicator and adjustment	w/indicator and adjustment
Electronic controls	●	●
Cycle status indicators	1 "Clean" light, 1 "Sanitized" light	1 "Clean" light, 1 "Sanitized" light
Selections/Enhancements	5/5	5/5
Last cycle memory	●	●
Audible end-of-cycle signal	●	●
Dedicated silverware jets	●	●
Selections		
DeepClean™ cycle	●	●
Anti-bacterial (NSF**)	●	●
Normal Wash	●	●
China/Crystal	●	●
Rinse only	●	●
Enhancements		
Steam Prewash	●	●
Delay Start	2/4/8-hour	2/4/8-hour
Added heat	●	●
Heated Dry	●	●
HotStart™	Automatic	Automatic
Control lock-out	●	●
Racking		
Rack finish	Eclipse black nylon	Eclipse black nylon
Adjustable upper rack with CleanTip tines	4-position	4-position
Removable upper rack†	Deep-tiered	Deep-tiered
Fold-down tine flexibility	2 multi-position upper, 2 lower	2 multi-position upper, 2 lower
Utility shelves	2 nylon StemSafe™	2 nylon StemSafe
Silverware basket	1-pc. with 3 cell covers	3-pc. with 3 cell covers
Solid surface install kit	Included	Included
Door handle	GE Café stainless	Sculptured
Dry		
Calrod® heating element	Multi-wattage	Multi-wattage
Fan-assist dry	●	●
Quiet		
Sound insulation package	TBD	TBD
Tube insulation—blanket	●	●
Door insulation	●	●
ActiveVent system	●	●
Tube collar trim	●	●
Weights and Dimensions		
Height w/legs retracted (in.)	34	34
Height w/legs removed (in.)	33-13/16	33-13/16
Overall width (in.)	24	24
Overall depth (in.)	24-3/4††	24-3/4†††
Approx. shipping wt. (lbs.)	105	105

*Subject to change.
**Based on DOE test procedure.
***Certified by National Sanitation Foundation.
†For best results, use shower nozzle attachment (sold separately) when upper rack is removed.
††Allow an additional 2.525" for the handle on CDWT980RSS series models.
†††Add 1/2" for deepest part of contour door. Allow an additional 2" for the handle on PDWT480/PDWT400 series models.

GE Profile built-in dishwasher

	GE Profile PDW7880PSS PDW7800PWW PDW7800PCC PDW7800PBB
2009 ENERGY STAR	●
Energy Factor (EF)*	0.68
Maximum gallons per cycle**	5.1
Kilowatt hrs/yr	321
Features	
Tube and door liner	PermaTuf®
Place settings	Up to 16
Front appearance	Contour door
Wash system	Six-level wash
Wash arms	3 direct-feed
Wash levels	6-towerless
Water filtration	3-stage, w/ExtraFine filter
Dual pumps and motors	●
Hard-foed disposer	Piranha
Sensor	CleanSensor
Automatic temperature control	●
Rinse aid dispenser	w/indicator & adjust.
Electronic controls	●
Cycle status indicators	Countdown display w/6 status lights
Selections/Enhancements	7/6
Last cycle memory	●
Audible end-of-cycle signal	●
Selections	
Anti-bacterial (NSF**)	●
Cookware	●
Normal Wash	●
China/Crystal	●
Glasses Cycle	●
SpeedCycle (wash & dry)	●
Rinse Only	●
Enhancements	
Delay Start	1-9-hour
Temp Boost	●
PreWash	●
Heated Dry	●
HotStart	●
Control lock-out	●
Racking	
Rack finish	White nylon
Adjustable upper rack with CleanTip tines	4-position deep-tiered
Fold-down tine flexibility	4 sets with 2 multi-position, upper, 2 lower
Utility shelves	4 with StemSafe
Silverware basket	3-pc. w/3 cell covers and ExtraBasket™
Solid surface install kit	Included
Latch	Squeeze
Dry	
Calrod heating element	Multi-wattage
Quiet	
Sound insulation package	54 dBA
Tube insulation—blanket	●
Door insulation	●
ActiveVent system	●
Tube collar trim	●
Weights & Dimensions	
Height w/legs retracted (in.)	34
Height w/legs removed (in.)	33-13/16
Overall width (in.)	24
Overall depth (in.)	24-3/4†
Approx. shipping weight (lbs.)	90

*Subject to change.
**Based on DOE test procedure.
***Certified by National Sanitation Foundation.
†Add 1/2" for deepest part of contour door.

GE® tall tub built-in dishwasher

	GE GDWT360RSS GDWT300RWW GDWT300RBB
2009 ENERGY STAR	●
Energy Factor (EF)*	0.66
Maximum gallons per cycle**	5.6
Kilowatt hrs/yr	324
Features	
SmartDispense technology	47 fl. oz.
Tube and door liner	Stainless steel
Place settings	Up to 16
Front appearance	Flat door
Full-length door design	●
Wash system	PureClean
Wash arms	3 direct-feed
Wash levels	6-towerless
Water filtration	5-stage with ExtraFine filter
Dual pumps and motors	●
Hard-foed disposer	Piranha
Sensor	CleanSensor
Rinse aid dispenser	w/indicator and adjustment
Electronic controls	●
Cycle status indicators	1 "Clean" light, 1 "Sanitized" light, 1 "Low detergent" light
Cycles/Options	3/5
Last cycle memory	●
Dedicated silverware jets	●
Cycles	
SaniWash (NSF**)	●
Normal Wash	●
Light wash	●
Options	
Delay Start	2/4/8-hour
Steam Prewash	●
Added Heat	●
Heated Dry	●
HotStart	Automatic
Control lock-out	●
Racking	
Rack finish	Platinum silver nylon
Upper rack	Deep-tiered
Utility shelves	2
Silverware basket	1-pc. w/3 cell covers
Solid surface install kit	Included
Latch	GE handle
Dry	
Calrod heating element	Multi-wattage
Fan-assist dry	●
Quiet	
Sound insulation package	TBD
Tube insulation—blanket	●
Mastic	●
ActiveVent system	●
Weights & Dimensions	
Height w/legs retracted (in.)	34
Height w/legs removed (in.)	33-13/16
Overall width (in.)	24
Overall depth (in.)	24-3/4
Approx. shipping wt. (lbs.)	105

*Subject to change.
**Based on DOE test procedure.
***Certified by National Sanitation Foundation.
†Legs not removable



GE Profile™ frontload washer

	GE Profile WPDH8900J
Capacity	
Capacity	Colossal
Cubic feet	4.2 IEC*
Features	
ENERGY STAR® qualified	●
CEE tier rating	3
ADA compliant	●
SmartDispense™	SPBD880J required
Liquid detergent dispenser	●
Fabric softener dispenser	●
Flow-Thru™ dispenser	Manual
Liquid or powder detergent	●
Bleach	●
Fabric softener	●
Wash/rinse temperatures	5 with sanitize
Water levels	Automatic
H2ition wash	●
HydroHeater™	●
SudsLogic	●
Number of cycles	Multiple
Specialty cycles	
Stain Inspector™	●
Fleece	●
Performance fabrics	●
Basket Clean	●
Fabric Refresh	●
SteamRefresh	●
Steam Assist	●
Special cotton care	●
Control type	Rotary electronic
End-of-cycle signal	Adjustable
Wash/spin speed combinations	8
RPM spin speed	1300
Water temperature system	HydroTemp™
Colors	●
Delicates	●
Wrinkle Free	●
Handwash	●
Whites	●
Optional soil levels	5
2nd rinse	●
Adaptive capabilities	Load size
Cycle countdown	Digital readout
Cycle status lights	LED
Delay start	24 hrs.
Drain and spin	●
Prewash	●
Washable wools	●
Active Wear	●
Speed Wash	●
Additional features	
Door style	See-thru glass
Noise package	Luxury
Wide-base suspension system	●
Leveling legs	●
Stainless steel wash basket	Tilted
Handle	TrueGrip™
Fill & drain hoses included	●
Storage pedestal available at additional cost	SPSD157J
Stacking kit available at additional cost	GEFLSTACK
Appearance	
Colors available**	WW, MV, MG
Weights & Dimensions	
Approx. shipping weight (lbs.)	250
Flexible installation	Undercounter, stacked, side-by-side
Power/Ratings	
Modified Energy Factor (MEF)	2.23
Water Factor (WF)	4.0
Circuit breaker or Time-delay fuse	15 or 20 amps
Volts/Hertz	120V; 60Hz

*Washes equivalent amount of clothes as a similar cu. ft. agitator machine, per IEC 60456 Edition 4.

**WW = White on white, MV = Vermillion Red, MG = Champagne.

GE Profile frontload dryer

	GE Profile DPVH890EJ/GJ
Capacity	
Capacity	Colossal
Cubic feet	7.5
Features	
ADA compliant	●
DuoDry™ system	●
Dual motors	●
Dual moisture sensor	●
Variable motor	●
Control type	Rotary-electronic
Cycle countdown	Digital readout
Cycle status lights	LED
Reverse tumble	●
Baffle Dry system	●
Heat selections	5 with Antibacterial
Number of cycles	Multiple
Specialty cycles	
Fleece	●
Performance fabrics	●
Speed dry	●
Cotton cycle	●
Custom cycle (my cycle)	●
Delicate cycle	●
Wrinkle Free	●
Mixed loads cycle	●
Antibacterial cycle	●
Active Wear	●
SteamRefresh	●
Steam Dewrinkle	●
Optional dryness levels	5
Timed dry—actual minutes on timer	15 to 90
Add Time	●
Additional features	
Damp dry signal	●
Dryer interior light	●
Delay start	24 hrs.
End-of-cycle signal	Adjustable
Door style	See-thru glass
Drum interior	Stainless steel
Leveling legs	●
Reverse-a-Door	●
Exhaust options (electric/gas)	4/3
Handle	TrueGrip
Extended venting capability	150'
Storage pedestal available at additional cost	SPSD157J
Appearance	
Colors available*	WW, MV, MG
Weights & Dimensions	
Approx. shipping weight (lbs.) E/G	138/143
Flexible installation	Undercounter, stacked, side-by-side
LP conversion kit	WE25M46

*WW = White on white, MV = Vermillion Red, MG = Champagne.

Dryer specifications

Exhaust options:

Electric: 4-way via rear, right, left and bottom.
Gas: For 7.5 cu. ft. dryers, when viewed from the front of the unit, exhaust 3-way via rear, left and bottom. Dryer is shipped exhausted to the rear. Alternate exhausting knockouts are supplied.

Circuit requirements:

Electric: An individual, properly grounded branch circuit, protected by a 30-amp circuit breaker or a time-delay fuse is required.

Electric dryer rating:

240V, 5600W, 24A, 60Hz—7.5 cu. ft. dryers
 208V, 4400W, 22A, 60Hz—7.0 cu. ft. dryers

Gas: An individual, properly grounded branch circuit, with a three-prong grounding-type receptacle, protected by a 15- or 20-amp circuit breaker or a time-delay fuse is required.

NEMA receptacle codes:

3-prong dryer cord/30A/4' long (cat #WX9X2) is for NEMA10-30R receptacle
 4-prong dryer cord/30A/4' long (cat #WX9X18) is for NEMA14-30R receptacle

GE® frontload washers

	GE WBVH5300K	WCVH4800K WCVH4815K
Capacity		
Capacity	King-size	Extra-large
Cubic feet	4.0 IEC*	2.6 IEC*
Features		
ENERGY STAR qualified	●	●
CEE tier rating	3	3
ADA compliant	●	●
Wash/rinse temperatures	4	5 with sanitize
Water levels	Automatic	Automatic
HydroHeater		●
HydroMotion™ wash	●	
SudsLogic	●	
Number of cycles	14	Multiple
Specialty cycles		Active wear
BasketClean™		●
Detergent dispenser (liquid/powder)	Flow-Thru timed	●
Bleach dispenser	Flow-Thru timed	●
Fabric softener dispenser	Flow-Thru timed	●
Control type	Electronic	Electronic
End-of-cycle signal	Adjustable	●
Wash/spin speed combinations	5	5
RPM spin speed	1000	1400
Water temperature system	PerfectTemp™	PerfectTemp
Colors	●	●
Delicates	●	●
Wrinkle free	●	●
Easy Care	●	●
Handwash	●	●
Whites	●	●
Heavy Duty	●	●
Optional soil levels	4	●
2nd rinse	●	●
Adaptive capabilities	Load size	Load size
Cycle countdown	with LED indicators	with LED indicators
Cycle status lights	●	●
Delay start	●	18 hrs
Drain and spin	●	●
Rinse and spin	●	●
Speed wash	●	●
Stain wash	●	●
Door style	See-thru glass	See-thru glass
Noise package	Quiet-by-Design	Deluxe quiet
Leveling legs	●	●
Stainless steel wash basket	●	●
Handle	TrueGrip	
Fill & drain hoses included	●	●
Pedestal available at additional cost	●	NA
Stacking kit available at additional cost	GEFLSTACK	GE24STACK
Appearance		
Colors available**	WW	WW MS
Weights & Dimensions		
Approx. shipping weight (lbs.)	225	159
Flexible installation	Undercounter, stacked, side-by-side	●
Power/Ratings		
Modified Energy Factor (MEF)	2.32	2.30
Water Factor (WF)	3.75	4.33
Circuit breaker or Time-delay fuse	15 or 20 amps	
Volts/Hertz	120V; 60Hz	

*Washes equivalent amount of clothes as a similar cu. ft. agitator machine, per IEC 60456 ratios.

**WW = White on white, MS = Metallic silver

Gas dryer electric rating:

120V, 60Hz, 6A

Gas (BTU/HR): 22,000 for 7.5 cu. ft. dryers. Factory-equipped for natural gas. Tested for LP gas. LP gas supply requires an optional conversion kit: 7.5 cu. ft. model kit is WE25M46. Have a qualified gas technician install a conversion kit. See dryer ducting information for proper installation.

Note: An extra-length (10 ft.) communication cable, Pub. No. 14-A013 is available for 7.5 and 7.3 cu. ft. dryers.

Dryer note: Dryer wall outlet must be located within 36" of service cord entry and accessible when dryer is mounted in position.

Stacked installation

• Brackets for stacking dryers, DPVH880EJ/GJ and DPVH890EJ/GJ are available at additional cost. Order part no. WE25X10028 or GEFLSTACK.

GE frontload dryers

	GE	
	DBVH520EJ/GJ	DCVH480EK DCVH485EK
Capacity		
Capacity	Super	Large
Cubic feet	7.0	4.0
Features		
ADA Compliant	●	●
Moisture sensor	Sensor Dry Plus™	Sensor Dry™
Control type	Rotary-electronic	Electronic
Cycle countdown	with LED indicators	with LED indicators
Cycle status lights	●	●
Dual thermistors	●	
Heat selections	4	5
Number of cycles	Multiple	Multiple
Cotton cycle	●	●
Specialty cycles		Active wear
Delicate cycle	●	●
Wrinkle free cycle		●
Easy Care cycle	●	
Mixed loads cycle	●	●
Antibacterial cycle		●
Optional dryness levels—Damp	●	
Optional dryness levels—Dry	●	
Optional dryness levels—Less dry	●	
Optional dryness levels—More dry	●	
Timed dry—actual minutes on timer	90	
Add Time	●	
Dewrinkle	●	
Speed dry		●
Timed dry	●	●
Air fluff		●
Warm up		●
Extended tumble		●
Dewrinkle		●
Damp dry signal		●
Dryer interior light		●
Clean lint filter reminder		●
Delay start		18 hours
Dryer interior light	●	
End-of-cycle signal	●	●
100% front serviceable	●	●
Door style	See-thru glass	See-thru glass
Noise package		Deluxe quiet
Drum interior	DuraDrum™	Stainless steel
Leveling legs	●	●
Reverse-a-Door	●	●
Exhaust options (electric/gas)	4/3	Rear, left, right, bottom
Handle	TrueGrip	
Pedestal available at additional cost	●	NA
Appearance		
Colors available*	WW	WW MS
Weights & Dimensions		
Approx. shipping weight (lbs.) E/G	125/130	99
Flexible installation	Undercounter, stacked, side-by-side	
LP conversion kit	WE25X0217	

*WW = White on white, MS = Metallic silver

GE Profile™ topload washer

	GE Profile
	WPGT9360E
Capacity	
Capacity cu. ft.	4.0 IEC* King-size
Energy	
ENERGY STAR qualified	●
CEE tier rating	1
Controls	
Electronic	LCD touchscreen display
Status indicators	LCD display
Cycle countdown	LCD
Adaptive capabilities	Water levels
HydroWash™	●
HydroHeater	●
Water temp system	HighTemp™
Wash/rinse temps	4
Water levels	Adaptive fill
Wash system	
Wash basket	Stainless steel
Wash mechanism	Infusor™
Wash/spin combinations	Multiple
Drive system	
Variable-speed motor	Direct drive
Maximum spin speed	1010 RPM
Dispensers	
Bleach	Flow-Thru timed
Fabric softener	Flow-Thru timed
Detergent	Flow-Thru timed
Wash Boost	Flow-Thru timed
Signals	
End-of-cycle	Variable
Wash cycles	
Number of cycles	Multiple
Custom cycles	6
Cycle selections	
Whites/cottons	●
Colors	●
Dark colors	●
Easy care	●
Handwash	●
Specialty cycles	Multiple
Program options	
Stain wash	Stain Inspector
Optional soil levels	5
Special cycles	
Delay start	●
SpeedWash	Quick clean
Prewash	●
2nd rinse	●
Extended spin	●
Rinse and spin	●
Spin only	●
Additional features	
Quiet performance	Supreme
HydroView™ glass lid	●
English/Spanish LCD option	●
Fill & drain hoses included	●
Appearance	
Backsplash color	Platinum or White
Colors available**	PL, WW
Weights & Dimensions	
Approx. shipping weight (lbs.)	155
Power/Ratings	
Modified Energy Factor (MEF)	1.98
Water Factor (WF)	7.1

*Washes equivalent amount of clothes as a similar cu. ft. agitator machine per IEC 60456 Edition 4.

**PL = Dark Platinum, WW = White on white.

GE Profile topload matching dryer

	Electric Gas	GE Profile
		DPGT750EC DPGT750GC
Capacity		
Capacity cu. ft.		7.3 King-size
Controls		
Electronic		●
Status indicators		LCD
Cycle countdown		LCD
Adaptive Logic™		●
Heat selections		5
Dry system		
Clothing moisture sensor		DuoDry
Temperature sensor		Dual thermistors
Dryer drum		Stainless steel
Drum baffles		Dark Platinum
Dual motors		●
Signals		
End-of-cycle		Variable
Dry cycles		
Number of cycles		Multiple
Custom cycles		6
Cycle selections		
Cottons		●
Mixed loads		●
Easy care		●
Knits/sweaters		●
Delicates		●
Specialty cycles		Multiple
Program options		
More dry		●
Dry		●
Less dry		●
Damp dry		●
Timed dry		
Time control		Electronic
Special cycles		
Drye® cycle		●
Delay start		●
Add time option		●
Dewrinkle		●
Quick Fluff (no heat)		●
Additional Features		
Quiet performance		Supreme
Quiet drum		●
Deluxe dryer rack		●
Dryer interior light		●
Extended venting capability		Up to 150 ft.
Clean lint filter reminder		●
English/Spanish LCD option		●
Reverse-a-Door		●
Appearance		
Backsplash color		Platinum or White
Colors available*		PL, WW
Weights & Dimensions		
Approx. shipping weight—elec. (lbs.)		155
Approx. shipping weight—gas (lbs.)		155
LP conversion kit		WE25X1004

*PL = Dark Platinum, WW = White on white.

Making builders' lives easier.



- An industry-leading company committed to customer satisfaction.
- GE has the leading position with builders, earning a #1 ranking in appliance preference by *Professional Builder* and *Professional Remodeler* for ten years!*
- A nationwide network of sales professionals and service technicians wholly dedicated to the builder community.
- 24-hour accessibility through award-winning technology
 - GECustomerNet.com
 - GESelectionCenter.com
 - GEAppliances.com
- GE Answer Center® saves you time by providing answers on product features.

**Professional Builder* and *Professional Remodeler* brand study, 1998-2006, 2008 (no study in 2007)



100 years of innovation and we're just getting started

For more than a century, GE has been committed to producing innovative products that change the way people live. The result of thorough research and rigorous testing, GE appliances are designed for years of dependable performance. Today, the GE tradition of quality and innovation continues.